

Safety Data Sheet

SOUDAL Soudabond Subfloor

Section 1. Identification

Product Identifier SOUDAL Soudabond Subfloor

Synonyms 137642 Manufacturer Stock 137642

Numbers

Recommended use Refer to Technical Information
Uses advised against Refer to Technical Information

Manufacturer Contact

Address Soudal

350 Ring RD

Elizabethtown, KY, 42701

USA

Phone Emergency Phone Fax

(270) 769-3385 (800) 424-9300 (270) 765-2412

CHEMTREC

Section 2. Hazards Identification

Classification CARCINOGENICITY - Category 2

FLAMMABLE AEROSOLS - Category 1

GASES UNDER PRESSURE - Liquefied gas SENSITIZATION - RESPIRATORY - Category 1

SERIOUS EYE DAMAGE /EYE IRRITATION - Category 2A

SKIN CORROSION/IRRITATION - Category 3

SPECIFIC TARGET ORGAN TOXICITY (Single Exposure) - Category 3

Signal Word Danger









Hazard Statements

Causes mild skin irritation
Causes serious eye irritation

Contains gas under pressure; may explode if heated

Extremely flammable aerosol

May cause allergy or asthma symptoms or breathing difficulties if inhaled May cause respiratory irritation; or May cause drowsiness or dizziness Suspected of causing cancer (state route of exposure if no other routes of exposure cause the hazard)

Precautionary Statements

Response

Prevention

Call a poison center or doctor if you feel unwell.

If experiencing respiratory symptoms: Call a poison center/doctor/ ...

If exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

If inhaled: If breathing is difficult, remove person to fresh air and keep

comfortable for breathing.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If skin irritation occurs: Get medical advice/attention. Avoid breathing dust/fume/gas/mist/ vapors/spray.

Do not handle until all safety precautions have been read and understood.

Do not spray on an open flame or other ignition source. In case of inadequate ventilation wear respiratory protection.

Keep away from heat.

Obtain special instructions before use.

Pressurized container: Do not pierce or burn, even after use.

Use only outdoors or in a well-ventilated area.

Wash thoroughly after handling. Wear eye protection/face protection.

Wear protective gloves/protective clothing/eye protection/face protection.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Protect from sunlight. Store in a well-ventilated place.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal Dispose of contents/container to Dispose of contents/container in accordance

with local, regional, national and international regulations.

Ingredients of unknown toxicity

0%

Hazards not Otherwise Classified

Persons already sensitized to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product is not to be used under conditions of poor ventilation. Gas/vapor spreads at floor level: Ignition hazard.

Section 3. Ingredients

CAS	Ingredient Name	Weight %
13674-84-5	2-Propanol, 1-chloro-, phosphate (3:1)	1% - 20%
25791-96-2	Glyceryl polypropylene glycol triether	1% - 20%
75-28-5	Isobutane	1% - 10%
115-10-6	Dimethyl ether	1% - 10%
74-98-6	Propane	1% - 10%
78-40-0	Triethyl phosphate	1% - 10%
101-68-8	4,4'-Diphenylmethane diisocyanate	> 25 %
9016-87-9	Polymeric diphenylmethane diisocyanate	> 25 %

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Inhalation	Remove victim from exposure area to fresh air. If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
Skin Contact	Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing. If eye irritation persists: Get medical attention.
Ingestion	Rinse mouth thoroughly with water. Do NOT induce vomiting. Get medical advice if you feel unwell.
Most Important Symptoms/Effects	Acute dry throat, sore throat Irritation to respiratory tract. May cause irritation of mucous membranes, runny nose, skin irritation, eye irritation, lacrimation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness.
	Delayed Suspected of causing cancer. May cause damage to organs through prolonged

or repeated exposure: liver, thyroid gland.

Indication of any immediate Treat symptomatically and supportively.

medical attention and special treatment needed

Section 5. Fire Fighting Measures

Suitable Extinguishing Media

ABC-powder, BC-powder

Unsuitable Extinguishing Media

CO2, water, foam

Special Hazards Arising from the Chemical

On burning: Releases toxic and/or corrosive gases. Extremely flammable aerosol. Pressurized container: may burst if heated.

Hazardous Combustion **Products**

Phosphorus oxides, nitrous vapors, hydrogen chloride, carbon monoxide,

carbon dioxide

Fire Fighting Measures

Move container from fire area if it can be done without risk. Damaged cylinders should be handled only by specialists. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. Do not direct water at source of leak or safety devices; icing may occur. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. ALWAYS stay away from tanks engulfed in fire.

Special Protective Equipment and

Wear full protective fire fighting gear including self contained breathing

apparatus (SCBA) for protection against possible exposure.

Precautions for Firefighters

Section 6. Accidental Release Measures

Personal Precautions. Protective Equipment and **Emergency Procedures**

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Up

Do not touch or walk through spilled material. Stop leak if you can do it without Containment and Cleaning risk. Do not direct water at spill or source of leak. Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. If possible, turn leaking containers so that gas escapes rather than liquid. Prevent entry into waterways, sewers, basements, or confined areas. Allow substance to evaporate. Ventilate the area.

Environmental Precautions Avoid release to the environment.

Section 7. Handling and Storage

Precautions for Safe Handling

Vapors are heavier than air. Observe good hygiene and safety practices when handling this product. Remove contaminated clothing and shoes immediately. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flame/hot surfaces - No smoking. Pressurized container: Do not pierce or burn, even after use. Do not spray on an open flame or other ignition sources. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Wear respiratory protection. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Do not eat, drink or smoke when using this product.

Conditions for Safe Storage, Including any

Store in a well-ventilated place. Keep container tightly closed.

Incompatibilities

Store locked up.

Protect from sunlight.

Do not expose to temperatures exceeding 50 °C/122 °F.

Store in a cool, dry area. Keep from direct sunlight. Ventilation at floor level. Store in fireproof room.

Keep unauthorized personnel away.

Shelf life is 10 months.

Incompatible Materials

No data available.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	2-Propanol, 1-chloro-, phosphate (3:1)	N/A	N/A	N/A
	Glyceryl polypropylene glycol triether	N/A	N/A	N/A
	Isobutane	1000 ppm	N/A	1000 ppm
	Dimethyl ether	N/A	400 ppm	N/A
	Propane	1000 ppm TWA	1000 ppm PEL	N/A
	Triethyl phosphate	N/A	N/A	N/A
	4,4'-Diphenylmethane diisocyanate	TWA: 0.005 ppm	Ceiling: 0.02 ppm Ceiling: 0.2 mg/m3	N/A
	Polymeric diphenylmethane diisocyanate	0.005 ppm	0.02 mg/m≈	N/A
Personal Protective Equipment	Goggles, Gloves			
ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)	There are no biological limit values for any of this product's components.			
Engineering Controls	Use explosion-proof lighting equipment. Ensure compliance with applicable exposure limits.			
Individual Protection Measures, such as	Eye/face protection Wear chemical safety goggles	S.		

Individual Protection Measures, such as Personal Protective Equipment

Skin Protection

Wear appropriate chemical resistant clothing. Wear fire/flame

resistant/retardant clothing. Refer to NFPA 2112, Standard on Flame-Resistant

Garments for Protection of Industrial Personnel Against Flash Fire and NFPA 2113, Standard on the Selection, Use, Care and Maintenance of Flame-

Resistant Garments for Protection of Industrial Personnel Against Short-

duration Thermal Exposures from Fire (2015).

Respiratory Protection

Respirators depend on exposure level. SCBA with full face piece recommended during change outs and available in case of emergency.

Glove Recommendations Wear appropriate chemical resistant gloves.

Section 9. Physical and Chemical Properties

Physical State	Aerosol	
Color	Not available	
Odor	Characteristic	
	odor	
Odor Threshold	Not available	
Solubility	Not available	
Partition coefficient Water/n-octanol	Not available	
VOC%	17.9%	
Viscosity	Not available	
Specific Gravity	0.982	
Density lbs/Gal	N/A	
Pounds per Cubic Foot	N/A	
Flash Point	Not available	
FP Method	N/A	
рН	Not available	
Melting Point	Not available	
Boiling Point	Not available	
Boiling Range	N/A	
LEL	N/A	
UEL	N/A	
Evaporation Rate	Not available	
Flammability	Extremely	
	flammable	
	aerosol	
Decomposition Temperature	Not available	
Auto-ignition Temperature	Not available	
Vapor Pressure	Not available	
Vapor Density	Not available	

Note

The above information is not intended for use in preparing product specifications. Contact Soudal before writing specifications.

Section 10. Stability and Reactivity

Reactivity May be ignited by heat, sparks or flames. Gas/vapor spreads at floor level:

Ignition hazard.

Chemical stability

Stable under normal conditions.

5 0.00

Possibility of Hazardous

Reactions

Will not occur.

Conditions to Avoid

Pressurized container: Do not pierce or burn, even after use. Do not spray on an

open flame or other ignition sources. Keep away from sources of ignition.

Incompatible Materials

Not available.

Hazardous Combustion

Phosphorus oxides, nitrous vapors, hydrogen chloride, carbon monoxide,

Products

carbon dioxide

Section 11. Toxicological Information

Information on Likely Routes of Exposure

Inhalation

Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness.

Skin Contact

Causes skin irritation. May cause an allergic skin reaction.

Eye Contact

Causes serious eye irritation.

Ingestion

No information on significant adverse effects.

Immediate Effects

dry throat, sore throat. Irritation to respiratory tract. May cause irritation of mucous membranes, runny nose, skin irritation, eye irritation, lacrimation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness.

Delayed Effects

Suspected of causing cancer. Causes damage to the respiratory system through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure: liver, thyroid gland.

Irritation/Corrosivity Data Respiratory Sensitization Causes skin irritation, eye irritation, respiratory tract irritation.

Dermal Sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Dermal Sensitization

May cause an allergic skin reaction.

Component Carcinogenicity

Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9

IARC:

Supplement 7 [1987]; Monograph 19 [1979] (Group 3 (not classifiable))

DFG:

Category 4 (no significant contribution to human cancer)

4,4'-Methylenediphenyl diisocyanate 101-68-8

IARC:

Monograph 71 [1999] ; Supplement 7 [1987] ; Monograph 19 [1979] (Group 3 (not

classifiable))

DFG:

Category 4 (no significant contribution to human cancer)

Germ Cell Mutagenicity

Tumorigenic Data

No information available for the product.

No information available for the product.

No information available for the product.

respiratory system

respiratory system, liver, thyroid gland

Specific Target Organ

Toxicity - Single Exposure

Specific Target Organ

Toxicity - Repeated

Exposure

Aspiration hazard No information available for the product.

Medical Conditions No information available for the product.

Aggravated by Exposure

Section 12. Ecological Information

Component Analysis - Aquatic Toxicity

2-Propanol, 1-chloro-, phosphate (3:1) 13674-84-5

Fish:

LC50 96 h Brachydanio rerio 56.2 mg/L [static]; LC50 96 h Pimephales promelas 98 mg/L [static]; LC50 96 h Poecilia reticulata 30 mg/L [static]

Algae:

EC50 72 h Desmodesmus subspicatus 45 mg/L IUCLID; EC50 96 h

Pseudokirchneriella subcapitata 4 mg/L IUCLID

Invertebrate:

EC50 48 h Daphnia magna 63 mg/L IUCLID

Section 13. Disposal

Disposal Methods Dispose of contents/container in accordance with local/regional/national

/international regulations.

Component Waste

Numbers

The U.S. EPA has not published waste numbers for this product's components.

Section 14. Transport Information

UN Number 1950

UN Proper Shipping Name Aerosols

DOT Classification Hazard Class: 2.1 Required Label(s): 2.1

Packing Group None assigned

IATA Information Shipping Name: AEROSOLS, FLAMMABLE

Hazard Class: 2.1 UN#: UN1950

Required Label(s): 2.1

IMDG Information Shipping Name: AEROSOLS

Hazard Class: 2 UN#: UN1950 Required Label(s): 2 **TDG Information**

Shipping Name: AEROSOLS

Hazard Class: 2.1 UN#: UN1950

Required Label(s): 2.1

Section 15. Regulatory Information

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA

process safety plan.

SARA

Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9

SARA 313: 1 % de minimis concentration

4,4'-Methylenediphenyl diisocyanate 101-68-8 SARA 313: 1 % de minimis concentration CERCLA: 5000 lb final RQ; 2270 kg final RQ

SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories

Flammable; Carcinogenicity; Acute toxicity; Skin Corrosion/Irritation;

Respiratory/Skin Sensitization; Serious Eye Damage/Eye Irritation; Specific

Target Organ Toxicity

U.S. State Regulations

The following components appear on one or more of the following state

hazardous substances lists:

Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9

NJ

4,4'-Methylenediphenyl diisocyanate 101-68-8

CA, MA, MN, NJ, PA

Dimethyl ether 115-10-6

MA, MN, NJ, PA

Isobutane 75-28-5

MA, NJ, PA

Propane 74-98-6 MA, MN, NJ, PA

California Prop 65

(IDL)

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects. For more information,

go to www.P65Warnings.ca.gov

Canadian WHMIS Ingredient Disclosure List

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL.

Section 16. Other Information

Revision Date

02/23/2024

Disclaimer

The data contained herein is based upon information that Soudal believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.