

Safety Data Sheet

SOUDAL Soudasil NFC

Section 1. Identification

Product Identifier SOUDAL Soudasil NFC

Synonyms TBD Manufacturer Stock TBD

Numbers

Recommended use Refer to Technical Information
Uses advised against Refer to Technical Information

Manufacturer Contact

Address Soudal Accumetric

350 Ring RD

Elizabethtown, KY, 42701

USA

Phone Emergency Phone Fax

(270) 769-3385 (800) 424-9300 (270) 765-2412

CHEMTREC

Section 2. Hazards Identification

Classification EYE DAMAGE/IRRITATION - Category 2A

HAZARDOUS TO THE AQUATIC ENVIRONMENT - LONG-TERM HAZARD -

Category 3

SENSITIZATION - SKIN - Category 1

SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) - Category 2

Signal Word Pictogram





Hazard Statements Causes serious eye irritation

Harmful to aquatic life with long lasting effects

May cause an allergic skin reaction

May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

Response Get medical advice/attention if you feel unwell.

If eye irritation persists: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

If on skin: Wash with plenty of soap and water. Wash contaminated clothing

before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Prevention Avoid breathing dust/fume/gas/mist/ vapors/spray.

Avoid release to the environment

Contaminated work clothing must not be allowed out of the workplace.

Do not breathe dust/fume/gas/mist/ vapors/spray.

Wash hands thoroughly after handling. Wear eye protection/face protection.

Wear protective gloves.

Storage N/A

Disposal Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Ingredients of unknown

toxicity

0%

Hazards not Otherwise

Classified

Additional Information None known

Section 3. Ingredients

| CAS | Ingredient Name | Weight % |
|-------------|---|-----------|
| 1760-24-3 | N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane | 1% - 5% |
| 2224-33-1 | Vinyl Oximino Silane | 1% - 5% |
| 22984-54-9 | Methyl Oximino Silane | 1% - 5% |
| 63148-62-9 | Dimethylpolysiloxane | 10% - 30% |
| 112945-52-5 | Amorphous fumed silica | 5% - 10% |
| 64741-44-2 | Distillates (petroleum), straight-run middle | 5% - 10% |

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Inhalation Remove to fresh air. If symptoms persist, obtain appropriate medical attention.

Ingestion Get medical attention.

Comments

Treat according to person's condition and specifics of exposure.

Section 5. Fire Fighting Measures

Suitable Extinguishing

Media

On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire

exposed containers.

Unsuitable Extinguishing

Media

None known

Auto-ignition Temperature Not determined Flammability Limits in Air Not determined Unusual Fire or Explosion None known

Hazards

Section 6. Accidental Release Measures

Containment/Clean Up Observe all personal protective equipment recommendations as described in

section eight. Collecr all spilled materials for disposal. This material is not classified as a hazardous waste per 40 CFR 261. State and local laws may

impose regulatory restrictions.

Section 7. Handling and Storage

Handling Avoid breathing vapors in top of shipping container. Keep container closed.

Use with adequate ventilation. Avoid contact with skin and clothing. Wash

throughly after handling.

Keep container closed and store in a cool, well ventilated area, away from Storage

water or moisture.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure

Limits

| Ingredient Name | ACGIH TLV | OSHA PEL | STEL |
|---|--------------|-------------|------|
| N-beta-(aminoethyl)-gamma- aminopropyltrimethoxysilane | N/A | N/A | N/A |
| Vinyl Oximino Silane | N/A | N/A | N/A |
| Methyl Oximino Silane | N/A | N/A | N/A |
| Dimethylpolysiloxane | N/A | N/A | N/A |
| Amorphous fumed silica | 10 mg/m3 | 6 mg/m3 | N/A |
| Distillates (petroleum), straight-run middle | | N/A | N/A |

Personal Protective

Equipment

Goggles, Gloves

Ventilation Local and general ventilation are recommended. Respiratory Protection If engineering controls do not maintain airborne concentrations of hazardous

ingredients below TLV, then a NIOSH/MSHA approved organic vapor respirator

should be used.

Eye Protection Wear safety glasses with side shields as a minimum.

Skin Protection Impervious gloves are suggested. Wash at mealtimes and end of shift.

Section 9. Physical and Chemical Properties

| Physical State | Paste |
|---------------------------------------|---------------|
| Color | Refer to |
| | product label |
| Odor | Slight |
| Odor Threshold | Not available |
| Solubility | Insoluble |
| Partition coefficient Water/n-octanol | Not available |
| VOC% | 41 g/L |
| | (3.76%) |
| Viscosity | 1,200,000 |
| | cPs |
| Specific Gravity | 1.01 |
| Density lbs/Gal | N/A |
| Pounds per Cubic Foot | N/A |
| Flash Point | > 52C |
| FP Method | Seta Closed |
| Ph | Not |
| | applicable |
| Melting Point | Not available |
| Boiling Point | Not available |
| Boiling Range | N/A |
| LEL | N/A |
| UEL | N/A |
| Evaporation Rate | Not available |
| Flammability | Not available |
| Decomposition Temperature | Not available |
| Auto-ignition Temperature | Not available |
| Vapor Pressure | Not available |
| Vapor Density | Not available |

Note The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

Section 10. Stability and Reactivity

Chemical Stability Stable
Hazardous polymerization Will not occur

Materials to Avoid / Oxidizing material can cause a reaction.

Incompatibility

Section 11. Toxicological Information

Carcinogen No
Teratogens No
Mutagens No
Reproductive Toxins No

Sensitizer Product releases MEKO, which is a potential skin sensitizer.

Component Toxicology

Information

Methyl Ethyl Ketoxime (MEKO) is formed upon contact with water or humid air. Male rodents exposed to MEKO vapor throughout their lifetime developed liver tumors. Since many commonly used chemicals cause liver tumors in rats and mice, additional testing is planned by the MEKO supplier to determine any relevance to humans. Until more data is known, exposure levels should be maintained as low as achievable.

Section 12. Ecological Information

Environmental Effects

Fate and Effects in Waste Water Treatment Plants

Water Treatment Plants
Environmental Fate and

Distribution

Complete information is not yet available. Complete information is not yet available.

Complete information is not yet available.

Section 13. Disposal

This material is not classified as a hazardous waste per 40 CFR 261. State and local laws may impose regulatory restrictions. Observe all federal, state, and local laws regarding waste disposal.

Section 14. Transport Information

UN Number N/A

UN Proper Shipping Name Caulking & Glaziers, NOI

DOT Classification None Packing Group N/A

Section 15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication

Standard 29 CFR 1910.1200.

TSCA Status All chemical substances found in this product comply with the Toxic

Substances Control Act inventory reporting requirements.

SARA Title III Section 302

Extremely Hazardous

Substances

None

SARA Title III Section 304

CERCLA Hazardous

Substances

Methanol (67-56-1)

Toxic Chemicals

SARA Title III Section 312

California Proposition 65

SARA Title III Section 313

Hazard Class

Acute: Yes Chronic: Yes Fire: No Pressure: No

Reactive: No

None

Canada Domestic

Substances List

All ingredients are listed on the DSL.

This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm:

None known

Massachusetts Silica, amorphous fumed (112945-52-5)

Methanol (67-56-1)

Hydroxy-terminated polydimethylsiloxane (70131-67-8) New Jersey

> Stoddard Solvent (8052-41-3) Aluminatrihydrate (21645-51-2) Polydimethylsiloxane (63148-62-9) Treated silica (67762-90-7) Methyl oximino silane (22984-54-9)

Methanol (67-56-1)

Pennslyvania Hydroxy-terminated polydimethylsiloxane (70131-67-8)

> Stoddard Solvent (8052-41-3) Aluminatrihydrate (21645-51-2) Polydimethylsiloxane (63148-62-9) Treated silica (67762-90-7)

> Methyl oximino silane (22984-54-9)

Methanol (67-56-1)

Section 16. Other Information

Revision Date 5/4/2017

Disclaimer The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to

> ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.