

BOSS 385 Professional Grade Plumber's Silicone Sealant

Safety Data Sheet



BOSS 380 Professional Grade Plumber's Silicone Sealant

Safety Data Sheet

Issue date: 08/06/2020 Revision date: 12/8/2022 Version: 2.0

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
Trade name : BOSS 385 Professional Grade Plumber's Silicone Sealant
Reference number : 142180, 142181, 142182, 142183, 142241, 160805

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Consumer use/Professional use
Use of the substance/mixture : Sealant

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Soudal
350 Ring Road
Elizabethtown, KY 42701
(270) 769-3385

technical@soudalaccumetric.com

www.SoudalUSA.com

1.4. Emergency telephone number

Emergency number : (800) 424-9300 CHEMTREC
24h/24h

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.2. Label elements

GHS classification in accordance with the OSHA Hazard communication Standard (29 CFR 1910.1200)

Hazard pictograms (CLP):

Signal word (CLP) : None needed
Contains :
Hazard Statements : Not a hazardous substance or mixture.
Precautionary Statements : Use only outdoors or in a well-ventilated area.

2.3. Other hazards

No data available.

SECTION 3: Ingredients

3.1. Substances

Not applicable

BOSS 385 Professional Grade Plumber's Silicone Sealant

Safety Data Sheet

3.2. Mixtures

Chemical nature: Silicone Elastomer

This product is a mixture.

Contains no hazardous ingredients according to GHS.

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|--|
| First-aid measures general | : First responders should pay attention to self-protection and used recommended clothing (chemical resistant gloves and splash protection). If potential for exposure exists, refer to section 8 for specific PPE. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell. |
| First-aid measures after skin contact | : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion | : Call a poison center or a doctor if you feel unwell. Do not induce vomiting unless directed to do so by medical personnel. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-------------------------------------|--|
| Symptoms/effects after skin contact | : Skin contact may aggravate existing dermatitis. Brief contact may cause slight skin irritation with local redness. May cause drying and flaking of the skin. |
| Symptoms/effects after eye contact | : May cause slight eye irritation. May cause mild discomfort. |

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|--------------------------------|--|
| Suitable extinguishing media | : Water spray. Dry powder. Alcohol-resistant Foam. Carbon dioxide. |
| Unsuitable extinguishing media | : None known. |

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire: Carbon oxides. Silicon oxides
Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health.

5.3. Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers. Evacuate area. Collect contaminated fire extinguishing water separately. Do not discharge into drains. Fire residues and contaminated fire extinguisher water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures: Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

BOSS 385 Professional Grade Plumber's Silicone Sealant

Safety Data Sheet

6.1.2. For emergency responders

Protective equipment

Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

6.2. Environmental precautions

Discharge into environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You need to determine which regulations are applicable. For large spills, provide diking and other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.

6.4. Reference to other sections

For further information refer to section 7, 8, 11, 12, and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes. Do not swallow. Avoid prolonged or repeated contact with skin. Take care to prevent spills, waste, and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep in properly labelled containers. Store in accordance with local, regional, and national regulations.

Incompatible products : Strong oxidizing agents

Unsuitable materials for containers : None known

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

BOSS 385 Professional Grade Plumber's Silicone Sealant

Safety Data Sheet

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses (w/ side shields)

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Use gloves chemically resistant to this material. Chlorinated polyethylene, neoprene, nitrile/butadiene rubber, polyethylene, ethyl vinyl alcohol laminate, polyvinyl chloride, Viton, polyvinyl alcohol, and butyl rubber. NOTICE: The selection of proper gloves for a particular application and duration of use in workplace should also take into account all relevant workplace factors such as, but no limited to: other chemicals which may be handled, physical requirements (cut/puncture resistant, dexterity thermal protection), potential body reactions to glove materials, as well as instructions/specifications provided by the glove supplier.

8.2.2.3. Respiratory protection

Respiratory protection:

Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or were indicated by your risk assessment process. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

The following types of air-purifying respirators should be effective: Organic vapor cartridge.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|----------------------|---|
| Physical state | : Paste |
| Color | : Various |
| Appearance | : Smooth Homogenous Paste |
| Odor | : Acetic Acid. |
| Odor threshold | : Not available |
| Melting point | : Not applicable |
| Freezing point | : Not available |
| Boiling point | : Not available |
| Flammability | : Not classified as a flammability hazard |
| Explosive properties | : Not available |
| Explosive limits | : Not available |

BOSS 385 Professional Grade Plumber's Silicone Sealant

Safety Data Sheet

| | |
|---|----------------------------------|
| Lower explosive limit (LEL) | : Not available |
| Upper explosive limit (UEL) | : Not available |
| Flash point | : Closed cup >100°C (212°F) |
| Auto-ignition temperature | Not available |
| Decomposition temperature | : Not available |
| pH | : Not applicable |
| Viscosity, kinematic | : Not available |
| Solubility | : Insoluble. |
| Partition coefficient n-octanol/water (Log Kow) | : Not available |
| Vapor pressure | : Not applicable |
| Vapor pressure at 50 °C | : Not available |
| Density | : 1,007 kg/m ³ (20°C) |
| Relative density | : 1.007 (20°C) |
| Relative vapor density at 20 °C | : Not available |
| Particle size | : Not applicable |
| Particle size distribution | : Not applicable |
| Particle shape | : Not applicable |
| Particle aspect ratio | : Not applicable |
| Particle aggregation state | : Not applicable |
| Particle agglomeration state | : Not applicable |
| Particle specific surface area | : Not applicable |
| Particle dustiness | : Not applicable |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients :

9.2.2. Other safety characteristics

VOC content : 23 g/L (< 3% by volume)

SECTION 10: Stability and reactivity

10.1. Reactivity

Not classified as a reactivity hazard

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Can react with strong oxidizing agents. When heated to temperatures above 150°C

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Avoid contact with oxidizing materials.

10.6. Hazardous decomposition products

Decomposition products can include and are not limited to: Formaldehyde.

SECTION 11: Toxicological information

11.1. Information on hazard classes

Acute toxicity (oral) Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts. As product single does LD50 has not been determined.
Based on information from component(s):
: LD50 >5,000 mg/kg Estimated

BOSS 385 Professional Grade Plumber's Silicone Sealant

Safety Data Sheet

| | |
|-----------------------------|--|
| Acute toxicity (dermal) | : Prolonged skin contact is unlikely to result in absorption of harmful amounts. As a product the dermal LD50 has not been determined. Based on information for the component(s): LD50 > 2,000 mg/kg Estimated |
| Acute toxicity (inhalation) | : Brief exposure (minutes) is not likely to cause adverse effects. Vapor from heated material may cause respiratory irritation. As product: The LC 50 has not been determined. |

Skin Corrosion/Irritation

Based on information for the component(s):
Prolonged exposure not likely to cause significant skin irritation.
May cause drying and flaking of the skin.

Serious eye damage/eye irritation

Based on information for the component(s):
May cause slight temporary eye irritation.
May cause mild eye discomfort.

Sensitization

For skin sensitization:
Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization:
No relevant information found.

Specific Target Organ Systemic Toxicity – Single Exposure

Evaluation of the available data suggests that this material is not a STOT-SE toxicant.

Specific Target Organ systemic Toxicity – Repeated Exposure

Based on available data for the component(s), repeated exposures are not anticipated to cause significant adverse effects.

Carcinogenic

No relevant data found

Teratogenicity

Contains component(s) which did not cause birth defects or any other fetal effects in lab animals.

Reproductive Toxicity

Contains component(s) which did not interfere with reproduction in animal studies.

Mutagenicity

In vitro genetic toxicity studies were negative for component(s) tested. Genetic toxicity studies in animals were negative for component(s) tested.

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological Information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulation Potential

No data available

12.4 Mobility in Soil

No data available

BOSS 385 Professional Grade Plumber's Silicone Sealant

Safety Data Sheet

SECTION 13: Disposal

13.1. Waste treatment methods

We make no guarantee or warranty of any kind that the use of disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with requirements and applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

SECTION 14: Transport Information

| | |
|----------------------------|---|
| UN Number: | N/A |
| UN Proper Shipping Name: | Not regulated as a dangerous good |
| DOT Classification: | Not regulated as a dangerous good |
| Packing Group: | Not regulated as a dangerous good |
| International Regulations: | UNRTDG Not regulated as a dangerous good |
| | IATA-DGR Not regulated as a dangerous good |
| | IMDG-Code Not regulated as a dangerous good |

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. US Federal Regulations

TSCA

All components of this product follow the inventory listing requirements of the US Toxic Substances and Control Act (TSCA) Chemical Substances Inventory.

SARA 311 and 312: No SARA hazards.

SARA 313: This material does not contain any chemicals with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

15.1.2. US State Regulations

Pennsylvania Right to Know

The following chemicals are listed because of the additional requirements for Pennsylvania law:

| Components | CAS Number |
|---|-------------|
| Polydimethylsiloxane hydroxy terminated | 70131-67-8 |
| Silicon dioxide | 7631-86-9 |
| Amorphous fumed silica | 112945-52-5 |

California Prop 65 Clear:

This product contains a chemical that is at or below the California Proposition 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

California Prop 65 Black:

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov

California Prop 65 Other Colors:

WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov

15.1.3. Canadian Regulations

DSL

All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

BOSS 385 Professional Grade Plumber's Silicone Sealant

Safety Data Sheet

Hazard Rating System

NFPA

| Health | Flammability | Instability |
|--------|--------------|-------------|
| 0 | 1 | 0 |

HMIS

| Health | Flammability | Instability |
|--------|--------------|-------------|
| 0 | 1 | 0 |

Disclaimer: The data contained herein is based upon information that Soudal believes to be reliable. Users of this product have the responsibility to determine the suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.