



SOUDAL Fix ALL High Tack

Safety Data Sheet

Reference number: 100000930

Issue date: 01/06/2022 Revision date: 23/09/2025 Supersedes version of: 16/10/2024 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : SOUDAL Fix ALL High Tack
Reference number : 175561

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Consumer use, Professional use
Use of the substance/mixture : Sealants

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Soudal USA
350 Ring Road
Elizabethtown, KY 42701

technical@soudalaccumetric.com

www.SoudalUSA.com

1.4 Emergency Telephone number

: (800) 424-9300 CHEMTREC
24h/24h

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Not classified

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

EUH-statements : EUH210 - Safety data sheet available on request.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Fix ALL High Tack

Safety Data Sheet

3.2. Mixtures

Name	Product identifier	%	Classification
trimethoxyvinylsilane	CAS-No.: 2768-02-7	< 1	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation: vapor), H332 (ATE=16.8 mg/l/4h) Skin Sens. 1, H317
Distillates (petroleum), straight-run middle	CAS-No.: 64741-44-2	≥ 1 – < 5	Asp. Tox. 1, H304
N-(3-(trimethoxysilyl)propyl)ethylenediamine	CAS-No.: 1760-24-3	< 5	Acute Tox. 4; Eye Dam. 1; Skin Sens. 1B; STOT RE 2; Aquatic Acute 2; H332, H318, H317, H373, H401
Calcium carbonate	CAS-No.: 1317-65-3	≥ 35 – < 55	
Diisononyl phthalate	CAS-No.: 28553-12-0	≥ 1 – < 5	Acute Tox. 4 (oral), H303 Reproductive Tox. 1B, H360FD Long term aquatic hazard 4, H413
Titanium Dioxide	CAS-No.: 13463-67-7	≥ 0 – < 5	

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Respiratory problems: consult a doctor/medical service.
First-aid measures after skin contact	: Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist if irritation persists.
First-aid measures after ingestion	: Rinse mouth out with water. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking
-------------------------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Fix ALL High Tack

Safety Data Sheet

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

6.1.2. For emergency responders

Protective equipment : Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically remove the product.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the workstation. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep container closed when not in use.

7.3. Specific end use(s)

No additional information available

Fix ALL High Tack

Safety Data Sheet

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methanol (CAS-no. 67-56-1)	
OSHA	
PEL	260 mg/m ³
PEL	200 ppm
ACGIH	
TWA	200 ppm

Distillates (Petroleum), straight-run middle (CAS-no. 64741-44-2)	
ACGIH	
TWA	200 mg/m ³

8.1.5. Control banding

No additional information available

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the workstation.

Personal protection equipment

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Safety glasses

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection: Protective gloves

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Thermal hazards

No additional information available

Environmental exposure controls

Fix ALL High Tack

Safety Data Sheet

Environmental exposure controls: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Color	: Variable.
Appearance	: Solid
Odor	: characteristic.
Odor threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not flammable
Upper explosion limit	: Not applicable
Flash point	: > 100 °C
Auto-ignition temperature	: Not applicable
Decomposition temperature	: Not available
pH	: Not available
pH solution	: Not available
Viscosity, kinematic	: Not applicable
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapor pressure	: Not available
Vapor pressure at 50°C	: Not available
Density	: 1.46 g/cm ³ (20°C)
Relative density	: Not available
Relative vapor density at 20°C	: Not applicable
Particle size	: Not available

9.2. Other information

Other safety characteristics

VOC content : < 1 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

Fix ALL High Tack

Safety Data Sheet

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard class

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

trimethoxyvinylsilane (2768-02-7)

LD50 oral rat	6,899 – 7,012 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	3,158 – 3,760 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	16.8 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapors), 14 day(s))

Distillates (Petroleum), straight-run middle (CAS-no. 64741-44-2)

LD50 oral rat	> 5,000 mg/kg
LD50 dermal rabbit	> 2,000 mg/kg

Calcium carbonate (1317-65-3)

LD50 oral (rat)	6,450 mg/kg
-----------------	-------------

Titanium Dioxide (13463-67-7)

LD50 oral (rat)	>10,000 mg/kg
-----------------	---------------

Diisononyl phthalate (28553-67-6)

LD50 oral (rat)	>10,000 mg/kg
LD50 dermal (rabbit)	>3,160 mg/kg
LC50 inhalation (rat)	>4.4 mg/L

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

LD50 oral rat	2,295 mg/kg bodyweight (EPA OPPTS 870.1100: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2,000 mg/kg bodyweight (EPA OPPTS 870.1200: Acute Dermal Toxicity, 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	1.49 – 2.44 mg/l air (EPA OPPTS 870.1300: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))

Fix ALL High Tack

Safety Data Sheet

Skin corrosion/irritation : Not classified

trimethoxyvinylsilane (2768-02-7)

pH	No data available in the literature
----	-------------------------------------

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

pH	10.2 (1 %)
----	------------

Serious eye damage/irritation : Not classified.

SOUDAL Fix ALL High Tack

Eye Irritation (test on mixture), Eye	No eye irritation (OECD 405 method)
---------------------------------------	-------------------------------------

trimethoxyvinylsilane (2768-02-7)

pH	No data available in the literature
----	-------------------------------------

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

pH	10.2 (1 %)
----	------------

Respiratory or skin sensitization : Skin sensitization: Not classified.

SOUDAL Fix ALL High Tack

Skin Sensitization (test on mixture), Skin, in vitro	Not sensitizing (OECD 497)
--	----------------------------

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

SOUDAL Fix ALL High Tack

Viscosity, kinematic	Not applicable
----------------------	----------------

trimethoxyvinylsilane (2768-02-7)

Fix ALL High Tack

Safety Data Sheet

Viscosity, kinematic	0.7 mm²/s (20 °C)
----------------------	-------------------

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

Viscosity, kinematic	3.1 mm²/s (20 °C, Calculated)
----------------------	-------------------------------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified.
Not rapidly degradable	

trimethoxyvinylsilane (2768-02-7)

LC50 - Fish [1]	191 mg/l (96 h, Oncorhynchus mykiss, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	169 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 89 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC chronic algae	89 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

LC50 - Fish [1]	597 mg/l (EU Method C.1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	81 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
EC50 72h - Algae [1]	126 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
ErC50 algae	8,8 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Selenastrum capricornutum, Static system, Fresh water, Experimental value, GLP)
NOEC chronic algae	3,1 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Selenastrum capricornutum, Static system, Fresh water, Experimental value, GLP)

Fix ALL High Tack

Safety Data Sheet

Distillates (Petroleum), straight-run middle (CAS-no. 64741-44-2)

LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	> 100 mg/l
EC50 72h - Algae [1]	> 100 mg/l
NOEC chronic fish	> 100 mg/l
NOEC chronic crustacea	> 100 mg/l

12.2. Persistence and degradability

trimethoxyvinylsilane (2768-02-7)

Persistence and degradability	not readily degradable in water.
-------------------------------	----------------------------------

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

Persistence and degradability	Not readily biodegradable in water.
-------------------------------	-------------------------------------

Distillates (Petroleum), straight-run middle (CAS-no. 64741-44-2)

Persistence and degradability	Readily biodegradable.
Biodegradation	74 % (OECD 301 F (Ready Biodegradability: Manometric Respirometry Test)28d)

12.3. Bioaccumulative potential

trimethoxyvinylsilane (2768-02-7)

Partition coefficient n-octanol/water (Log Pow)	1.1 (QSAR, KOWWIN, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

Partition coefficient n-octanol/water (Log Pow)	0.2 (QSAR, KOWWIN, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Distillates (Petroleum), straight-run middle (CAS-no. 64741-44-2)

Partition coefficient n-octanol/water (Log Pow)	> 7.2
---	-------

12.4. Mobility in soil

trimethoxyvinylsilane (2768-02-7)

Fix ALL High Tack

Safety Data Sheet

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.8 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	-0.6 (log Koc, QSAR)
Ecology - soil	Highly mobile in soil.

12.5. Results of PBT and vPvB assessment

Fix ALL High Tack

The product does not meet the PBT and vPvB classification criteria

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

We make no guarantee or warranty of any kind that the use of disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with requirements and applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing product should be done only after careful evaluation and in compliance with all federal, local and state laws.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID /

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated for transport				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

Fix ALL High Tack

Safety Data Sheet

14.4. Packing group

Not regulated

Not regulated

Not regulated

Not regulated

Not regulated

14.5. Environmental hazards

Not regulated

Not regulated

Not regulated

Not regulated

Not regulated

No supplementary information available

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air Transport

Not regulated

Inland Waterway Transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. US Federal Regulations

TSCA

All components of this product follow the inventory listing requirements of the US Toxic Substances and Control Act (TSCA) Chemical Substances Inventory.

SARA 302

None

SARA 304

None

SARA 311/312

Acute Health Hazard

Yes

Chronic Health Hazard

Yes

Fire Hazard

No

Sudden Release of Pressure Hazard

No

Reactive Hazard

No

SARA 313

None present of none present in reportable quantities.

15.1.2. US State Regulations

Massachusetts

Calcium Carbonate (1317-65-3)

Titanium Dioxide (13463-67-7)

Diisononyl phthalate (28553-67-6)

New Jersey

Calcium Carbonate (1317-65-3)

Titanium Dioxide (13463-67-7)

Diisononyl phthalate (28553-67-6)

Pennsylvania

Calcium Carbonate (1317-65-3)

Titanium Dioxide (13463-67-7)

Fix ALL High Tack

Safety Data Sheet

Diisononyl phthalate (28553-67-6)

California Prop 65: WARNING: This product can expose you to chemicals including titanium dioxide, which is known to the State of California to cause cancer, and methanol, which is known to the State of California to cause birth defects and other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic

Fix ALL High Tack

Safety Data Sheet

PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation: vapor)	Acute toxicity (inhalation: vapor) Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3

Full text of H- and EUH-statements:

H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1

Disclaimer: The data contained herein is based upon information that Soudal believes to be reliable. Users of this product have the responsibility to determine suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.