Safety Data Sheet



Soudafoam All Season Foam Gun Grade

Safety Data Sheet

Issue date: 04/17/2025 Supercedes: 11/15/2024 Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : Soudafoam All Season Foam Gun Grade

Reference number : 128390 Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Main use category : Consumer use, Professional use

Use of the substance/mixture : Polyurethane

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Soudal 350 Ring Road Elizabethtown, KY 42701 T (270) 769-3385 www.SoudalUSA.com

1.4. Emergency telephone number

Emergency number Chem Trec (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aerosol, Category 1	H222
Flammable Gas, Category 1	H229
Gases under Pressure – liquified gas	H280
Acute toxicity (inhalation: dust, mist), Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Respiratory sensitization, Category 1	H334
Skin sensitization, Category 1	H317
Carcinogenicity, Category 2	H351
Specific target organ toxicity — Single exposure, Category 3,	H335
Respiratory tract irritation	
Specific target organ toxicity — Repeated exposure, Category 2	H373

Adverse physicochemical, human health and environmental effects

Pressurized container: May burst if heated. Extremely flammable aerosol. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

04/17/2025 (Version: 3.0) 1/13

Safety Data Sheet

2.2. Label elements



Hazard pictograms (CLP)

GHS02 GHS07 GHS08 GHS04

Signal word (CLP) : Danger

Hazardous ingredients : polymethylene polyphenyl isocyanate

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurized container: May burst if heated.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H332 - Harmful if inhaled.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 - May cause respiratory irritation. H351 - Suspected of causing cancer.

H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P308+P313 - IF exposed or concerned: Get medical advice/attention.

P405 - Store locked up.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

Extra phrases : Persons already sensitized to diisocyanates may develop allergic reactions when using this

product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including

dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

2.3. Other hazards

The product does not meet the PBT and vPvB classification criteria.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

OLI MIXIMO					
	Name	Product identifier	%	Classification	

04/17/2025 (Version: 2.0) 2/13

Safety Data Sheet

polymethylene polyphenyl isocyanate	(CAS-No.) 9016-87-9	≥ 25 – < 50	Carc. 2, H351 Resp. Sens. 1, H334 Skin Sens. 1, H317 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
reaction products of phosphoryl trichloride and 2methyloxirane	(CAS-No.) 1244733-77-4	≥10 - < 20	Acute Tox. 4 (Oral), H302
dimethyl ether (Propellant gas (Aerosol))	(CAS-No.) 115-10-6	≥ 5 – < 10	Flam. Gas 1A, H220 Press. Gas
isobutane (Propellant gas (Aerosol))	(CAS-No.) 75-28-5	≥ 5 – < 10	Flam. Gas 1A, H220 Press. Gas
propane (Propellant gas (Aerosol))	(CAS-No.) 74-98-6	≥ 5 – < 10	Flam. Gas 1A, H220 Press. Gas (Liq.), H280

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if

you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a

doctor if you feel unwell.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash

occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation

May cause respiratory irritation. May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurized container: May burst if heated.

04/17/2025 (Version: 3.0) 3/13

Safety Data Sheet

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting

: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures

: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

. .

Leave the product to solidify. Mechanically recover the product. Carefully collect the spill/leftovers. Notify authorities if product enters sewers or public waters. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

Other information

: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not

breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area.

Avoid contact with skin and eyes.

Hygiene measures

Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always

wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked

up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Incompatible products

: Heat sources. Ignition sources. Strong bases. Strong acids.

Packaging materials

: Aerosol.

04/17/2025 (Version: 2.0) 4/13

Safety Data Sheet

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

dimethyl ether (115-10-6)	
AIHA WEEL (TWA)	1,000 ppm (8 hours)

polymethylene polyphenyl isocyanate (9016-87-9)

ACGIH (TWA)	0.005 ppm

Propane (74-98-6)

NIOSH REL (TWA)	1,800 mg/m³; 1,000 ppm (10 hours)

OSHA PEL (TWA) 1,800 mg/m³; 1,000 ppm (8 hours)

Isobutane (75-28-5)

NIOSH REL (TWA)	1,900 mg/m³; 800 ppm (10 hours)
ACGIH TLV (STEL)	1,000 ppm (15 min)

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):







Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

04/17/2025 (Version: 3.0) 5/13

Safety Data Sheet

Physical state : Liquid Appearance : Aerosol. Color : Variable. characteristic. Odor Odor threshold : No data available рΗ : No data available Relative evaporation rate (butylacetate=1) : No data available Melting point : Not applicable Freezing point : No data available Boiling point : No data available : No data available Flash point : No data available Auto-ignition temperature Decomposition temperature : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Vapor pressure : No data available Relative vapor density at 20 °C : No data available : 1.047 (20°C) Relative density : 1047 kg/m³ (20°C) Density Solubility : No data available : No data available Partition coefficient n-octanol/water (Log Pow) Viscosity, kinematic : No data available : No data available Viscosity, dynamic

Explosive properties : Pressurized container: May burst if heated.

Oxidizing properties : No data available Explosive limits : No data available

9.2. Other information

VOC content : < 17.9 % (175 g/l)

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurized container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

04/17/2025 (Version: 2.0) 6/13

Safety Data Sheet

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified

dimeth	d other	(445.4	0 6)
aimeur	vi ether (110-1	ט-ט

LC50 Inhalation - Rat [ppm] 164000 ppm (4 h, Rat, Male, Experimental value, Inhalation (gases), 14 day(s))

propane (74-98-6)

LC50 Inhalation - Rat [ppm] > 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))

isobutane (75-28-5)

LC50 Inhalation - Rat [ppm] > 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))

polymethylene polyphenyl isocyanate (9016-87-9)

LD50 oral rat	> 10000 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Literature study, Dermal)

reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)

	· · · · · · · · · · · · · · · · · · ·
LD50 oral rat	632 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 7 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an

allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Suspected of causing cancer.

polymethylene polyphenyl isocyanate (9016-87-9)

IARC group 3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Soudafoam Fireblock Gun

Vaporizer Aerosol

SECTION 12: Ecological information

12.1. Toxicity

04/17/2025 (Version: 3.0) 7/13

Safety Data Sheet

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Not classified

(chronic)

Not rapidly degradable

Not rapidly degradable		
dimethyl ether (115-10-6)		
LC50 - Fish [1]	> 4100 mg/l (NEN 6504: Water - Determination of toxicity with Poecilia reticulata, 96 h, Poecilia reticulata, Semi-static system, Fresh water, Experimental value, Lethal)	
EC50 - Crustacea [1]	> 4400 mg/l (NEN 6501: Water - Determination of toxicity with Daphnia magna, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Lethal)	
EC50 96h - Algae [1]	154,9 mg/l (ECOSAR v1.00, Algae, QSAR)	
propane (74-98-6)		
LC50 - Fish [1]	49,9 mg/l (96 h, Pisces, Fresh water, QSAR, Estimated value)	
EC50 96h - Algae [1]	11,89 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)	
isobutane (75-28-5)		
LC50 - Fish [1]	27,98 mg/l (ECOSAR v1.00, 96 h, Pisces, Fresh water, QSAR)	
EC50 96h - Algae [1]	8,57 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)	
polymethylene polyphenyl isocyanate (9016-87-9)		
LC50 - Other aquatic organisms [1]	> 1000 mg/l (96 h, Literature study)	
reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)		
LC50 - Fish [1]	51 mg/l Pimephalis promelas	
EC50 - Crustacea [1]	131 mg/l Daphnia magna	
EC50 72h - Algae [1]	82 mg/l Pseudokirchnerella subcapitata	
NOEC chronic crustacea	32 mg/l	
NOEC chronic algae	13 mg/l	
12.2. Persistence and degradability		

dimethyl ether (115-10-6)	
Persistence and degradability	not readily degradable in water.
propane (74-98-6)	
Persistence and degradability	Readily biodegradable in water.

isobutane (75-28-5)

04/17/2025 (Version: 2.0) 8/13

Safety Data Sheet

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

polymethylene polyphenyl isocyanate (9016-87-9)		
Persistence and degradability	not readily degradable in water.	
reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)		
Persistence and degradability	not readily degradable in water.	
Biodegradation	14 % OECD 301E	
12.3. Bioaccumulative potential		
dimethyl ether (115-10-6)		
Partition coefficient n-octanol/water (Log Pow)	0,1 (Experimental value)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
propane (74-98-6)		
Partition coefficient n-octanol/water (Log Pow)	1,09 – 2,8 (Experimental value, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
isobutane (75-28-5)		
Partition coefficient n-octanol/water (Log Pow)	1,09 – 2,8 (Experimental value, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
polymethylene polyphenyl isocyanate (9016-87-9)		
BCF - Fish [1]	1 (Pisces, Literature study)	
Partition coefficient n-octanol/water (Log Pow)	10,46 (Calculated, KOWWIN)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)		
BCF - Fish [1]	0,8 – 14	
Partition coefficient n-octanol/water (Log Pow)	2,68	
12.4. Mobility in soil		

dimethyl ether (115-10-6)	
Ecology – soil	Not applicable (gas).
propane (74-98-6)	
Ecology – soil	Not applicable (gas).
isobutane (75-28-5)	

04/17/2025 (Version: 3.0) 9/13

Safety Data Sheet

Ecology – soil	Not applicable (gas).
polymethylene polyphenyl isocyanate (9016-87-9)	
Partition coefficient n-octanol/water (Log Koc)	9,078 – 10,597 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology – soil	Product adsorbs onto the soil.
reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)	
Partition coefficient n-octanol/water (Log Koc)	2,24

12.5. Results of PBT and vPvB assessment

Soudafoam Fireblock Gun

The product does not meet the PBT and vPvB classification criteria

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations

Additional information

Waste treatment methods

Ecology - waste materials

European List of Waste (LoW) code

- $: \ \, \text{Dispose of contents/container in accordance with licensed collector's sorting instructions}.$
- : Do not discharge into drains or the environment.
- : Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.
- : Avoid release to the environment.
- : 08 05 01* waste isocyanates
 - 16 05 04^* gases in pressure containers (including halons) containing dangerous substances
 - 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID /

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	umber			
Not regulated for transport				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

04/17/2025 (Version: 2.0) 10/13

Safety Data Sheet

14.5. Environmental hazards Not regulated Not regulated Not regulated Not regulated Not regulated No supplementary information available

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air Transport

Not regulated

Inland Waterway Transport

Not regulated

Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. US Federal Regulations

TSCA

All components of this product follow the inventory listing requirements of the US Toxic Substances and Control Act (TSCA) Chemical Substances Inventory.

No

SARA 302 None **SARA 304** None **SARA 311/312** Yes Acute Heath Hazard Chronic Health Hazard Yes Fire Hazard No Nο

Sudden Release of Pressure Hazard Reactive Hazard

SARA 313 None present of none present in reportable quantities.

15.1.2. US State Regulations

Massachusetts

Calcium Carbonate (1317-65-3) Titanium Dioxide (13463-67-7) Diisononyl phthalate (28553-67-6)

New Jersey

Calcium Carbonate (1317-65-3) Titanium Dioxide (13463-67-7) Diisononyl phthalate (28553-67-6)

Pennsylvania

Calcium Carbonate (1317-65-3) Titanium Dioxide (13463-67-7)

04/17/2025 (Version: 3.0) 11/13

Safety Data Sheet

Diisononyl phthalate (28553-67-6)

California Prop 65: WARNING: This product can expose you to chemicals including titanium dioxide, which is known to the State of California to cause cancer, and methanol, which is known to the State of California to cause birth defects and other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation (EC) No 1907/2006

04/17/2025 (Version: 2.0) 12/13

Safety Data Sheet

RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation: vapor)	Acute toxicity (inhalation: vapor) Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Full text of H- and EUH-statements:	
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1

Disclaimer: The data contained herein is based upon information that Soudal believes to be reliable. Users of this product have the responsibility to determine suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.

04/17/2025 (Version: 3.0) 13/13