

BOSS[®]
PRO**333**
FOAM

GAP FILLING STRAW & GENIUS GUN

BOSS[®]333

Gap Filling Foam is a ready-to-use, multi-purpose, polyurethane foam that expands to three times its original volume on contact with air. The expanding action fills holes, cracks and gaps more completely than standard caulks.

COLORS:**Straw Can**

142212 - Tan

Genius Gun Can

143104 - Tan

FEATURES:

- UL Classified, Tested to ASTM E-84
- Triple expanding
- Weatherproofs against wind and moisture
- Fills gaps, cracks, and holes
- Can be sanded, painted, and stained
- VOC Compliant

THE IDEAL SEALANT/ADHESIVE FOR:

- Air sealing
- Partition walls with ceilings
- Through penetrations around cables and pipes
- Seams between chimneys, roof protection, roof panels and wall panels,

PACKAGING:

- 12 oz. Straw Can
- 20 oz. Genius Gun Can

Scan the QR Code to see the full line of **BOSS[®]PRO** Products!



Visit Our Website

www.bossproducts.com

BOSS[®]
PRO**333**
FOAM

GAP FILLING STRAW & GENIUS GUN

TYPICAL PROPERTIES	STRAW CAN	GENIUS GUN
Density	1.25 lbs./ft ³	1.56 lbs./ft ³
Thermal Conductivity	0.22 - 0.26 Btu-in/hr-F-ft ²	0.22 - 0.26 Btu-in/hr-F-ft ²
R Value	3.9 - 4.1 per inch	3.9 - 4.1 per inch
Skin Formation (1" bead)	10 minutes (73°F & 50% RH)	10 minutes (73°F & 50% RH)
Fully Cured (1" bead)	24 hours (73°F & 50% RH)	24 hours (73°F & 50% RH)
Cuttable (1" bead)	90 minutes (73°F & 50% RH)	90 minutes (73°F & 50% RH)
Fire Testing	Flame Spread-15 Smoke Developed-35	Flame Spread-15 Smoke Developed-35
Theoretical Yield	3.8 gal	5.8 gal
Water Absorption	1%	1%
Service Temperature	-40°F to 194°F	-40°F to 194°F
Application Temperature	40°F to 95°F	40°F to 95°F

*These values may vary depending on environmental factors such as temperature, humidity, and type of substrate.

Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal Accumetric.

LIMITATIONS

- Ground shipments only. Cannot ship by air. Reactive VOC 175 g/l (17% wt).

CAUTION

EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE. Turn off all pilot lights, electrical igniters, burners and other sources of ignition or heat during use. Do not smoke, use matches or lighters while dispensing foam. Do not expose to direct sunlight, high heat or store in enclosed vehicle. Avoid breathing vapor/spray. Use only outdoors or in a well ventilated area with appropriate breathing apparatus. Avoid contact with skin and eyes. Wearing eyewear and gloves is recommended. Do not incinerate or puncture can. Store at temperatures below 120°F. KEEP OUT OF REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS). FIRST AID: In case of eye contact, flush immediately with water for 15 minutes and get medical help. If inhalation causes physical discomfort, move to fresh air. If discomfort persists or any breathing difficulty occurs, get medical help. If swallowed, drink large quantities of water. DO NOT induce vomiting. GET PHYSICIAN ASSISTANCE IN ALL CASES. Cured foam is not harmful to health.

SOUDAL
Soudal AccumetricCall The
BOSS[®]**800-928-BOSS**350 Ring Road • Elizabethtown • KY 42701
(270) 769-3385 • 800-928-2677 • Fax: (270) 765-2412
www.bossproducts.com