

**BOSS<sup>®</sup>**  
**PRO****ALL SEASONS****125**  
**MULTI-SEAL**

# SEALANT / ADHESIVE

## ROOFING, GUTTERS, METAL

**BOSS<sup>®</sup> 125 Multi-Seal<sup>®</sup>**

construction sealant is a multi-purpose, one part sealant, formulated with USP™ Technology. This unique sealant is free from solvents and isocyanates. It cures on exposure to atmospheric moisture to form a highly durable flexible sealant. **BOSS<sup>®</sup> 125 Multi-Seal<sup>®</sup>** has been formulated to offer outstanding primerless adhesion to most common building materials including vinyl, aluminum, steel, concrete, wood and glass. It can be applied and tooled under most weather conditions.

**COLORS:****Cartridge**

- 142900 - White
- 158853 - Arctic White
- 142892 - Limestone
- 142898 - Tan
- 142897 - Stone
- 142887 - Aluminum/Grey
- 142890 - Grey
- 142895 - Redwood Tan
- 142891 - Hunter Green
- 142889 - Brown
- 142893 - Medium Bronze
- 142896 - Special Bronze
- 142888 - Black
- 142899 - Translucent

**PACKAGING:**

- 9.5 oz. Cartridge
- 1 Gallon Pail
- Other sizes available upon request

Scan the QR Code to see the full line of **BOSS<sup>PRO</sup>** Products!

**FEATURES:**

- VOC compliant
- Bonds to Kynar<sup>®</sup> 500\*
- Bonds to wet, damp surfaces
- Plastic cartridge
- Long lasting, flexible adhesive
- Many colors available
- Paintable in under an hour\*\*
- Qualifies for LEED credits

\*Kynar 500<sup>®</sup> is a trademark of Arkema Inc.

\*\*Test small area for compatibility before painting

**THE IDEAL SEALANT/ADHESIVE FOR:**

- Metal
- Flashing
- Asphalt Shingles
- Gutters
- Downspouts
- Vents
- Tiles
- Wood
- Roofing
- Curbs
- Door & Window Perimeter Joints
- Aluminum Angle Joints
- Masonry Joints
- Many More...



Visit Our Website

[www.bossproducts.com](http://www.bossproducts.com)

**BOSS<sup>®</sup>**  
**PRO****ALL SEASONS****125**  
**MULTI-SEAL**

# SEALANT / ADHESIVE

## ROOFING, GUTTERS, METAL

TYPICAL PROPERTIES	Colors	Translucent
<b>Uncured</b>		
Flow Sag or Slump	NIL	NIL
Tack Free Time	30 min	20 min
Extrusion Rate	400 g/min	300 g/min
<b>Cured-Physical 7 Days at 77°F (25°C) and 50% RH (1/8" thickness)</b>		
Durometer Shore A Hardness	45 points	17 points
Specific Gravity	1.53	1.01
Tensile Strength	245 psi	180
Elongation	350%	550%
Modulus	130 psi	55 psi
Shrinkage	NIL	NIL
Service Temperature		-40°F to 200°F
Application Temperature		-35°F to 140°F
*These values may vary depending on environmental factors such as temperature, humidity, and type of substrate. Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal Accumetric.		

### LIMITATIONS

- Do not use for structural glazing
- It is the sole responsibility of the user to test the adhesion to the substrate for suitability

### CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

**SODAL**

Soudal Accumetric

Call The  
**BOSS<sup>®</sup>****800-928-BOSS**350 Ring Road • Elizabethtown • KY 42701  
(270) 769-3385 • 800-928-2677 • Fax: (270) 765-2412  
[www.bossproducts.com](http://www.bossproducts.com)