

BOSS[®]
PRO**QUICK GRAB****180****MULTI-SEAL**

INSULATION ANCHOR PIN ADHESIVE

BOSS[®] 180Multi-Seal[®]

Insulation Anchor Pin Adhesive is a one component, moisture curing adhesive for adhering anchor pins to rigid boards, fibrous semi-rigid board, masonry walls, ducts, metal buildings, painted and galvanized surfaces. **BOSS[®] 180** Multi-Seal[®] has immediate grab and high bond strength allowing insulation to be hung in 24 hours. Check an anchor pin before hanging insulation to be sure it is secure. Cure times vary with humidity. **BOSS[®] 180** Multi-Seal[®] forms a strong bond even on damp surfaces.

COLORS:

Cartridge

143017 - White

FEATURES:

- VOC compliant
- Adheres 200 pins
- Excellent thermal shock resistance
- Water resistant
- Immediate grab and high bond strength
- Low odor
- Primerless adhesion to damp and non-porous surfaces
- Qualifies for LEED credits

THE IDEAL SEALANT/ADHESIVE FOR:

- Rigid Boards
- Fibrous Semi-Rigid Boards
- Masonry Walls
- Ducts
- Metal Buildings
- Painted & Galvanized Surfaces

PACKAGING:

- 9.5 oz. Cartridge
- Other sizes available upon request

Scan the QR Code to see the full line of **BOSS^{PRO}** Products!



Visit Our Website

www.bossproducts.com

BOSS[®]
PRO**QUICK GRAB****180**
MULTI-SEAL

INSULATION ANCHOR PIN ADHESIVE

TYPICAL PROPERTIES

| Uncured | |
|--|----------------|
| Specific Gravity | 1.30 |
| Sag/Slump | NIL |
| Tack Free | 20-25 min. |
| Cure Time at 75°F (24°C) and 50% RH (3/8" thick) | 24 hrs. |
| Extrusion Rate | 225 g/min. |
| Cured-Physical | |
| Tensile Strength | 220 psi |
| Elongation | 400% |
| Durometer, Shore A Hardness | 35 points |
| Service Temperature | -40°F to 325°F |
| Application Temperature | -35°F to 140°F |
| *These values may vary depending on environmental factors such as temperature, humidity, and type of substrate. Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal Accumetric. | |

LIMITATIONS

- Some protective coatings may not allow required adhesion
- It is the sole responsibility of the user to test the adhesion to the substrate for suitability
- New concrete surfaces need to cure a minimum of 28 days in order to ensure best adhesion

CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

SODAL

Soudal Accumetric

Call The
BOSS[®]**800-928-BOSS**350 Ring Road • Elizabethtown • KY 42701
(270) 769-3385 • 800-928-2677 • Fax: (270) 765-2412
www.bossproducts.com