

BOSS[®]
PROOUTSTANDING
BOND STRENGTH**185**
MULTI-SEAL

FAST CURE ADHESIVE

BOSS[®] 185

Multi-Seal[®] Fast Cure Adhesive is a one component, high performance adhesive/sealant formulated with USP™ technology. Provides excellent durability, maximum adhesive strength and is VOC compliant in 50 states. It is color stable and UV resistant (non-yellowing) and contains no isocyanates solvents halogens or acids. It is a moisture curing sealant that remains flexible, even at low temperatures with quick grab strength and excellent adhesion to various substrates such as aluminum, steel, glass, wood, brick concrete, mirrors and many plastics. It is also paintable with most latex paints.

COLORS:

Cartridge

143121 - White

FEATURES:

- Immediate high grab strength to most substrates
- Plastic cartridge
- Formulated with USP™ technology
- Paintable with most latex paints*
- Can be applied on wet surfaces
- UV Resistant and color stability
- VOC compliant
- Qualifies for LEED credits
- Low odor

THE IDEAL SEALANT/ADHESIVE FOR:

- Aluminum
- Steel
- Glass
- Wood
- Brick
- Concrete
- Mirrors
- Many Plastics

PACKAGING:

- 9.5 oz. Cartridge
- Other sizes available upon request

Scan the QR Code to see the full line of **BOSS^{PRO}** Products!



Visit Our Website

www.bossproducts.com

BOSS[®]
PROOUTSTANDING
BOND STRENGTH**185**
MULTI-SEAL

FAST CURE ADHESIVE

TYPICAL PROPERTIES

Uncured

Appearance	Smooth
Color	White
Specific Gravity	1.45
Sag/Slump	NIL
Extrusion Rate	250 g/min.
Tack Free Time at 75°F (24°C) and 50% RH	20 min.

Cured-Physical

Durometer, Shore A Hardness	55 points
Ultimate Tensile Strength	400 psi
Elongation	300%
Modulus	250 psi
Solid	98%
Service Temperature	-40°F to 200°F
Application Temperature	-35°F to 140°F

*These values may vary depending on environmental factors such as temperature, humidity, and type of substrate.

Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal Accumetric.

LIMITATIONS

- Do not use for structural glazing
- Do not use for window glazing
- Not recommended for use on PE, PP or PTFE (Teflon) due to poor adhesion to these substrates
- Not recommended for applications below the water line, continuous immersion or for sealing/ bonding windshields
- Poor resistance to solvents, concentrated acids & chlorinated hydrocarbons
- It is the sole responsibility of the user to test the adhesion to the substrate for suitability

CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

Call The
BOSS[®]

800-928-BOSS

350 Ring Road • Elizabethtown • KY 42701
(270) 769-3385 • 800-928-2677 • Fax: (270) 765-2412
www.bossproducts.com

SODAL
Soudal Accumetric