

**BOSS<sup>®</sup>**  
**PRO****231****SEALANT/ADHESIVE**

# ROOFING GUTTERS METAL

**BOSS<sup>®</sup> 231**

is a plasto-elastic, paintable, one-component repair sealant based on copolymers,

**BOSS<sup>®</sup> 231** has excellent adhesion on bitumen, asphalt, hardened concrete, metal, glass, brick, wood, plastics and Kynar<sup>®</sup> 500\*. **BOSS<sup>®</sup> 231** is also suited for wet, non-absorbing surfaces, and is ideally suited for waterproofing cracks in roofs, gutters, skylights, chimneys, walls, etc. **BOSS<sup>®</sup> 231** is resistant to U.V. exposure and temperatures up to 200°F.

**COLORS:**

Cartridge

146432 - Clear

**FEATURES:**

- Exceptional elongation and flexibility
- Asphalt shingle compatible
- Easily applied, non-stringing formulation
- Tools and cleans up easily
- Excellent adhesion to many building surfaces, even when damp
- Totally transparent, crystal clear
- Solvent based
- Can be painted over after curing \*
- UV resistant, waterproof and resistant to weathering

\*Kynar 500<sup>®</sup> is a trademark of Arkema Inc.

\*\*Test small area for compatibility before painting

**THE IDEAL SEALANT/ADHESIVE FOR:**

- Asphalt Shingles
- Coated Steel
- Concrete
- Vinyl
- Steel
- Wood
- Plastics
- Roofing/Shingles
- Other Common Roofing Substrates

**PACKAGING:**

- 10.1 oz. Cartridge

Scan the QR Code to see the full line of **BOSS<sup>PRO</sup>** Products!



Visit Our Website

[www.bossproducts.com](http://www.bossproducts.com)

**BOSS<sup>®</sup>**  
**PRO**

# ROOFING GUTTERS METAL

**231**  
**SEALANT/ADHESIVE****TYPICAL PROPERTIES**

Basis	Styrene Acrylate
Consistency	Paste
Curing system	Physical drying
Skin formation*	(73°F/50% R.H.) Ca. 10 min.
Density	Ca. 0.95 g/ml.
Maximum allowed distortion	10 %
Service Temperature	-4°F to 200°F
Application Temperature	40°F to 90°F
Shrinkage	Ca. 20%

\*These values may vary depending on environmental factors such as temperature, humidity, and type of substrate.

Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal Accumetric.

**LIMITATIONS**

- Do not use for structural glazing
- Do not use as a window glazing sealant
- Not recommended for use on PE, PP or PTFE (Teflon®) due to poor adhesion to these substrates

**CAUTION**

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

Call The  
**BOSS<sup>®</sup>**

**800-928-BOSS**

350 Ring Road • Elizabethtown • KY 42701  
(270) 769-3385 • 800-928-2677 • Fax: (270) 765-2412  
[www.bossproducts.com](http://www.bossproducts.com)

  
**Soudal**  
Soudal Accumetric