

BOSS[®]
PRO

7 YEAR

355
CAULK

GENERAL PURPOSE ACRYLIC LATEX

BOSS[®] 355

7 Year General

Purpose Latex Caulk was

designed for interior use. **BOSS[®] 355** cures

to form a flexible, non-yellowing seal without staining

or bleeding and is compatible with a wide variety of substrates.

BOSS[®] 355 7 Year General Purpose Latex Caulk was developed for use around windows, door frames, baseboards or any joint or gap where a weather-tight seal is required. **BOSS[®] 355** adheres well to wood, masonry, brick and plaster.

COLORS:

Cartridge

143194 - White

FEATURES:

- VOC Compliant
- Paintable
- Interior
- Plastic cartridge

THE IDEAL SEALANT/ADHESIVE FOR:

- Wood
- Masonry
- Brick
- Plaster

PACKAGING:

- 9.5 oz. Cartridge

Scan the QR Code to see the full line of **BOSS^{PRO}** Products!



Visit Our Website

www.bossproducts.com

BOSS[®]
PRO**7 YEAR****355****CAULK**

GENERAL PURPOSE ACRYLIC LATEX

TYPICAL PROPERTIES

Colors	White
% Non-Volatile, by weight	83.5%
% Volume Shrinkage: ASTM C-733-87	28%
Weight, approximate	14.4 lb/gal 1.7135 kg/L
pH	7.0-8.7
Slump	0"
Tack-Free Time: ASTM D-2377-84	25 minutes
Elongation	235%
Volatile Organic Content (VOC minus water)	8.6 grams/liter
Service Temperature	-20°F to 185°F
Application Temperature	40°F to 110°F

*These values may vary depending on environmental factors such as temperature, humidity, and type of substrate.

Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal Accumetric.

LIMITATIONS

Do not use for structural glazing

It is the sole responsibility of the user to test the adhesion to the substrate for suitability

Nonreactive VOC 8.6 g/l (<1.5% wt.)

CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

Call The
BOSS[®]

800-928-BOSS

350 Ring Road • Elizabethtown • KY 42701
(270) 769-3385 • 800-928-2677 • Fax: (270) 765-2412
www.bossproducts.com

SODAL

Soudal Accumetric