

BOSS[®]
PRO**WATER
WEATHER
PROOF****389**
SILICONE

MARINE PROFESSIONAL GRADE

BOSS[®] 389

Marine Silicone is a one-part, fungicidal, silicone rubber sealant formulated to provide outstanding performance in a variety of boat building and maintenance applications. Excellent for use on windshields, deck hardware, joints, cracks, port holes and through hull fittings. **BOSS[®] 389** bonds well to aluminum, non-oily woods, glass, metal, fiberglass, painted surfaces and many plastics.

COLORS:**Cartridge**

- 143022 - Clear
- 143023 - White
- 143021 - Black

FEATURES:

- Permanently flexible
- Non-yellowing
- Unaffected by sunlight, weathering, most chemicals and solvents
- Will not shrink or sag
- Waterproof/weatherproof seal
- Mildew resistant

THE IDEAL SEALANT/ADHESIVE FOR:

- Windshields
- Deck Hardware
- Joints
- Cracks
- Port Holes
- Through Hull Fittings
- Aluminum
- Non-oily Woods
- Glass
- Metal
- Fiberglass
- Painted Surfaces
- Many Plastics
- Many More...

PACKAGING:

- 10.1 oz. Cartridge
- Other sizes available upon request

Scan the QR Code to see the full line of **BOSS^{PRO}** Products!



Visit Our Website

www.bossproducts.com

BOSS[®]
PRO**WATER
WEATHER
PROOF****389**
SILICONE

MARINE PROFESSIONAL GRADE

TYPICAL PROPERTIES

Slump	NIL
Tack Free Time at 77°F (25°C) and 50% RH	10-20 min
Cured - Physical 7 Days at 77°F (25°C) and 50% RH (1/8" thickness)	
Elongation	415%
Durometer Shore A Hardness	23 points
Tensile Strength	325 psi
Movement Capacity	±25%
Extrusion Rate	410 g/min.
Service Temperature	-40°F to 400°F
Application Temperature	-35°F to 140°F

LIMITATIONS

BOSS® 389 Marine Silicone is not recommended for continuous water immersion, nor for floor joints where abrasion and physical abuse are encountered. It should not be applied to:

- Porous surfaces such as masonry
- Building materials that bleed oils or solvents, such as impregnated wood and certain partially vulcanized rubber gaskets, tapes or adhesives
- Totally confined spaces, because the sealant needs atmospheric moisture to cure

CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE, AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. Sealant releases acetic acid (vinegar-like odor) during cure. KEEP OUT OF THE REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

Call The
BOSS[®]

800-928-BOSS

350 Ring Road • Elizabethtown • KY 42701
(270) 769-3385 • 800-928-2677 • Fax: (270) 765-2412
www.bossproducts.com

SODAL
Soudal Accumetric