

BOSS[®]
PROLONG LIFE
RELIABILITY**535****POLYURETHANE**

PROFESSIONAL GRADE MULTI-PURPOSE CONSTRUCTION

BOSS[®] 535

Polyurethane Sealant is a high quality, elastic, one-component professional grade based on polyurethane. **BOSS[®] 535** is very easy to apply, and offers good weather and UV resistance. It remains permanently elastic after curing. It does not bubble in high temperature and humidity, and is formatted to adhere very well to many materials.

COLORS:**Cartridge**

- 144575 - White
- 144557 - Black
- 144691 - Grey
- 144580 - Limestone
- 147029 - Aluminum Grey
- 144597 - Medium Bronze
- 147184 - Off White
- 147028 - Redwood Tan
- 147212 - Stone
- 144163 - Tan
- 147027 - Special Bronze

FEATURES:

- 50% movement
- VOC compliant
- ASTM C920, class 50
- Bonds to Kynar 500[®]*
- Mildew resistant
- Paintable **
- Stays flexible
- UV & weather resistant
- Qualifies for LEED credit
- Non-yellowing and non-staining
- Non-streaking
- Free from solvents and isocyanates
- No bubble formation within sealant (in high temperature and humidity applications)

*Test small area for compatibility before painting

** Kynar 500[®] is a trademark of Arkema Inc.**THE IDEAL SEALANT/ADHESIVE FOR:**

- High Movement Building And Construction Joints
- Window Frames
- Door Frames
- Concrete
- Seal Shrinking Joints In Concrete Floors
- Floor Joints
- Wood
- Many More...

PACKAGING:

- Standard Cartridges

Scan the QR Code to see the full line of **BOSS^{PRO}** Products!



Visit Our Website

www.bossproducts.com

BOSS[®]
PROLONG LIFE
RELIABILITY**535****POLYURETHANE**

PROFESSIONAL GRADE MULTI-PURPOSE CONSTRUCTION

TYPICAL PROPERTIES

Uncured

Flow Sag or Slump	NIL
Skin Time	50-60 min
Cured-Physical 7 Days at 77°F (25°C) and 50% RH (1/8")	
Durometer Shore A Hardness	30±5 points
Specific Gravity	1.53
Tensile Strength	165 psi
Elongation	> 800%
Modulus	85 psi
Shrinkage	NIL
Service Temperature	-22°F to 194°F
Application Temperature	41°F to 86°F

*These values may vary depending on environmental factors such as temperature, humidity, and type of substrate.

Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal Accumetric.

LIMITATIONS

- It does not adhere to glass, PE, PP, or PTFE (Teflon). It is recommended that you test adhesion on every surface.
- Do not apply in the presence of uncured silicone sealants, alcohol, or other solvent cleaners.
- Contact with bitumen, tar or other plasticizer releasing materials such as EPDM, neoprene, butyl, etc. is to be avoided since it can give rise to discoloration and loss of adhesion.

CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).


Soudal AccumetricCall The
BOSS[®]**800-928-BOSS**350 Ring Road • Elizabethtown • KY 42701
(270) 769-3385 • 800-928-2677 • Fax: (270) 765-2412
www.bossproducts.com