

**BOSS<sup>®</sup>**  
**PRO****FAST TACK**  
EVEN AT LOW TEMPERATURES**635C**  
**ADHESIVE**

# CONTACT

## PROFESSIONAL GRADE

**BOSS<sup>®</sup> 365C**

Spray Adhesive

is an extremely versatile, fast drying adhesive for both temporary and permanent bonding. Its wide web spray pattern is suitable for your toughest adhesive applications with materials such as leather, cardboard, most plastics and cloth. This high solids product is ideal for uneven or porous surfaces and is waterproof, flexible and transparent.

**BOSS<sup>®</sup> 635C** is used for clean, efficient and economical permanent subfloor bonding in building and construction. It does not contain CFC's or HCFC's.

**COLORS:****Spray Canister**

144668 - Clear

**FEATURES:**

- VOC Compliant
- Multi Purpose
- Non-Chlorinated
- Fast Drying
- High Strength
- Web Spray
- Formulated with high solids
- Prop 65 compliant

**THE IDEAL SEALANT/ADHESIVE FOR:**

- Fabric
- Plastic
- Felt
- Cork
- Foam
- Insulation
- Paper
- Corrugated
- Wood
- Metal
- Rubber
- Leather
- MANY MORE...

**PACKAGING:**

- 12 oz. Spray Canister

Scan the QR Code to see the full line of **BOSS<sup>PRO</sup>** Products!



Visit Our Website

[www.bossproducts.com](http://www.bossproducts.com)

**BOSS<sup>®</sup>**  
**PRO****FAST TACK**  
EVEN AT LOW TEMPERATURES**635C**  
**ADHESIVE**

# CONTACT

## PROFESSIONAL GRADE

### TYPICAL PROPERTIES

Base	Single Component Polyurethane
Consistency	Physical drying
Curing System	Moisture Cure At Room Temperature
Curing Time (*)	About 4 hours
Skin Formation (*)	About 20 minutes
Full Strength (*)	About 24 hours
Post expansion	Minimal
Shear Strength (Wet Lumber) (ASTM D3498)	205 psi
Shear Strength (Dry Lumber) (ASTM D3498)	283 psi
Shear Strength (Frozen Lumber) (ASTM D3498)	587 psi
Moisture Resistance (ASTM D3498)	316 psi
Temperature Resistance	-20°F to +100°F
UL 723 (ASTM E 84) Fire Test	Flame spread 15, Smoke developed 35

\*These values may vary depending on environmental factors such as temperature, humidity, and type of substrate.

Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal Accumetric.

### LIMITATIONS

- Not watertight

### CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF THE REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

**SODAL**

Soudal Accumetric

Call The  
**BOSS<sup>®</sup>****800-928-BOSS**350 Ring Road • Elizabethtown • KY 42701  
(270) 769-3385 • 800-928-2677 • Fax: (270) 765-2412  
[www.bossproducts.com](http://www.bossproducts.com)