

BOSS[®]
PRO**AIRTIGHT
SEAL****826****ACOUSTICAL**

SMOKE & SOUND SEALANT

BOSS[®] 826

Acoustical Smoke &

Sound Sealant is a one-part, non-flammable, latex based product formulated to reduce sound and smoke transmission in all types of wall partition systems. **BOSS[®] 826** is a non-staining, non-migrating formulation that adheres well to most substrates including wood, metal, concrete and gypsum board. **BOSS[®] 826** Acoustical Smoke & Sound Sealant creates a tough, elastic seal against sound, air infiltration (drafts), smoke and moisture.

COLORS**Cartridge**

142862 - White

Sausage

158294 - White

Pail

142863 - White

FEATURES

- Greatly reduces sound transmissions through walls and other partitions
- Strongly adheres to most substrates
- May be caulked, knifed or troweled
- Non-flammable – 0 flame spread
- Quick and easy application
- Soap and water clean-up
- Won't stain or migrate
- Permanently flexible
- Paintable when dry
- VOC compliant
- Water resistant
- STC Rating 53
- Low odor

THE IDEAL SEALANT/ADHESIVE FOR

- Heating / AC Ducts & Cold Air Returns
- Exposed or Unexposed Joints, Walls, Ceilings, Floors & Partition Systems
- Veneer Plaster Systems
- Electrical Boxes & Cutouts
- Masonry / Brick
- Gypsum Board
- Concrete
- Metal
- Wood

PACKAGING

- 29 oz. Cartridge
- 20 oz. Sausage
- 4.5 Gallon Pail

Scan the QR Code to
see the full line of
BOSS^{PRO} Products!



Visit Our Website

www.bossproducts.com

BOSS[®]
PRO**AIRTIGHT
SEAL****826****ACOUSTICAL**

SMOKE & SOUND SEALANT

TYPICAL PROPERTIES

Base	Acrylic latex	
Sag	No sag in vertical displ. @120°F	ASTM C639
STC Rating	53 (Sound Transmission Class)	
Curing system	Moisture evaporation	
Skin Formation *	+/- 15 minutes	@ 75°F & 50% relative humidity
Tack-free time *	30 minutes	ASTM D 2377-84
% Non-volatile	80%	
Shrinkage	30%	ASTM C 733-87
pH	7.0 - 9.0	
Movement capability	Moderate joint movement	
Service temperature range	20°F to +185°F	
Application temperature range	+40°F to +110°F	
Shelf life	12 months	Stored between 41°F & 77°F
VOC	10 g/L	

*These values may vary depending on environmental factors such as temperature, humidity, and type of substrate.

Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal Accumetric.

LIMITATIONS

- Soudal recommends a preliminary compatibility test, especially on PVD and non-porous materials.
- Not recommended for continuous water immersion.
- Not recommended for vehicular or foot traffic.
- This product is not to be used as a structural glazing sealant.

CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

Call The
BOSS[®]

800-928-BOSS

350 Ring Road • Elizabethtown • KY 42701
(270) 769-3385 • 800-928-2677 • Fax: (270) 765-2412
www.bossproducts.com

SODAL
Soudal Accumetric