

Soudabond Subfloor

SOUDAL

- Gun applied Fast Curing PU Collapsible Foam Adhesive
- 100% Solvent Free
- For Interior and Exterior Use
- Time & Money Saving Application
- One 29oz Can Replaces Up to 12 Quart Tubes of Solvent Based Adhesive
- Protects Against Squeaks by Forming a Tight Seal
- Can be Applied to Wet, Dry, or Frozen Lumber
- Meets ASTM D3498
- VOC Compliant
- Excellent Adhesion to:
 - Concrete
 - Masonry
 - Metals
 - Treated Lumber
 - Decking
 - Plywood
 - OSB
 - Etc.



Bonding of Subfloors Wood to Wood Assemblies

This information and all further technical advice are based on SOUDAL present knowledge and experience. However, SOUDAL assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, SOUDAL disclaims all WARRANTIES EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. SOUDAL SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. SOUDAL reserves the right to make any changes according to technological progress or further developments.



SOUDAL

(*) Measured at 68 °F / 65 % R.H. These values may vary depending on ambient factors such as temperature, humidity and type of substrate.

- Excellent adhesion on most substrates, except for PTFE, PE and PP.
- Lower temperature and humidity will extend curing time.

KEEP OUT OF REACH OF CHILDREN. For professional use only. KEEP AWAY FROM HEAT (>49°C), SPARKS AND OPEN FLAME. DO NOT PUNCTURE OR INCINERATE CAN. DO NOT EXPOSE TO DIRECT SUNLIGHT. USE ONLY IN WELL VENTILATED AREAS. In case of eye contact, flush eye with water for 15 minutes and get immediate medical attention. For inhalation, move to fresh air. For skin contact, wash thoroughly with water and soap. If swallowed, drink large quantities of water, but do not induce vomiting. Call a physician immediately. Refer to SDS for further information.

SOUDAL FEATURES

