

Soudacryl Firestop

SOUDAL

- In Case of Fire, Forms a Flexible Shield Preventing the Spread of Fire, Smoke and Toxic Gases Through Construction Openings
- Remains Flexible When Cured
- Excellent Adhesion Properties
- Easy Clean-Up With Water
- Service Temp: -20°F – 185°F
- VOC Compliant
- Both Interior and Exterior Applications
- Tested Systems Up to 2 Hours
- Meets ASTM E-814 (UL 1479)

Wall & Floor Penetrations Construction Openings



This information and all further technical advice are based on SOUDAL present knowledge and experience. However, SOUDAL assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. SOUDAL disclaims all WARRANTIES EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. SOUDAL SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. SOUDAL reserves the right to make any changes according to technological progress or further developments.

Soudacryl Firestop



Base	Acrylic latex	
Sag	No sag in vertical displ. @120°F	ASTM C639
Curing system	Moisture evaporation	
Tooling time (*)	+/- 15 minutes	@ 75°F & 50% relative humidity
Tack-free time (*)	30 minutes	ASTM D 2377-84
% Non-volatile	80%	
Shrinkage	30%	ASTM C 733-87
pH	7.0 - 9.0	
Movement capability	Moderate joint movement	
Service temperature range	-20°F to +185°F	
Shelf life	12 months	Stored between 41°F & 77°F
VOC	8.6 g/L	

(*) These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. Test results are averages obtained under laboratory conditions. Reasonable variations can be expected.

Limitations:

- Soudal recommends a preliminary compatability test, especially on PVD and non-porous materials.
- Not recommended for continuous water immersion.
- Not recommended for vehicular or foot traffic.
- This product is not to be used as a structural glazing sealant.

CAUTION:

KEEP OUT OF REACH OF CHILDREN. Avoid skin and eye contact. On contact, uncured sealant could cause irritation to skin and eyes. In case of eye contact, flush eyes with warm water for 15 minutes, call a physician. For skin contact, remove sealant with a paper towel. If swallowed, do not induce vomiting, call a physician. Soudacryl Firestop is manufactured for professional use only. Refer to Safety Data Sheet (SDS) for further information.

PLEASE REFER TO TECHNICAL DATA SHEET FOR COMPLETE INFORMATION ABOUT THE PRODUCT

SEE UL TESTED SYSTEMS FOR INSTALLATION INSTRUCTIONS



Distributed by: **Soudal Accumetric** • 350 Ring Road, Elizabethtown, KY 42701 • info@soudalusa.com • 877-873-8739 • www.soudalusa.com

SoudacrylFirestop/072417