

# Soudacryl C834

**SOUDAL**

- Siliconized Latex Acrylic
- Permanent Color
- Paintable\*
- Mildew Resistant
- UV Resistant
- Easy Clean-up With Water
- Non-yellowing
- Very Easy Application
- VOC Compliant
- Colors: White, Almond, Limestone, Aluminum Stone, Beige-Grey, Ivory, Tan, Cedar, Brown, Bronze, Black
- Meets ASTM C834
- Excellent Adhesion to:
  - Wood
  - Drywall
  - Masonry
  - Metal
  - Brick
  - Glass
  - Concrete



**Moderate Movement Joints**  
**Window & Door Joints**  
**Crown Molding**

This information and all further technical advice are based on SOUDAL present knowledge and experience. However, SOUDAL assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. SOUDAL disclaims all WARRANTIES EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. SOUDAL SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. SOUDAL reserves the right to make any changes according to technological progress or further developments.

# Soudacryl C834



Base	Acrylic latex	
Sag	No sag in vertical displ. @120°F	ASTM C639
Curing system	Moisture evaporation	
Skin Formation (*)	+/- 10 minutes	@ 75°F & 50% relative humidity
Tack-free time (*)	< 1 hour	ASTM C 679
% Non-volatile	61% (clear) – 81% (colors)	
Shrinkage	28%	ASTM C 733-87
pH	8.0	
Movement capability	Moderate joint movement	
Service temperature range	-20°F to +185°F	
Application temperature range	+40°F to +110°F	
Shelf life	12 months	Stored between 41°F & 77°F
VOC	28 g/L	

(\*) These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. Test results are averages obtained under laboratory conditions. Reasonable variations can be expected.

### Limitations:

- Soudal recommends a preliminary compatibility test, especially on PVD and non-porous materials.
- Not recommended for continuous water immersion.
- Not recommended for vehicular or foot traffic.
- This product is not to be used as a structural glazing sealant.

### CAUTION:

KEEP OUT OF REACH OF CHILDREN. Avoid skin and eye contact. On contact, uncured sealant could cause irritation to skin and eyes. In case of eye contact, flush eyes with warm water for 15 minutes, call a physician. For skin contact, remove sealant with a paper towel. If swallowed, do not induce vomiting, call a physician. Soudacryl C834 is manufactured for professional use only. Refer to Safety Data Sheet (SDS) for further information.

PLEASE REFER TO TECHNICAL DATA SHEET FOR COMPLETE INFORMATION ABOUT THE PRODUCT

## SOUDAL FEATURES



Distributed by: Soudal Accumetric • 350 Ring Road, Elizabethtown, KY 42701 • info@soudalusa.com • 877-873-8739 • www.soudalusa.com

SoudacrylC834/071119