

RED GREASE SPRAY PART NO. 143508

SPECIFICATIONS

Physical State	Aerosol
Color/Appearance	Bright red viscous liquid
Odor	Hydrocarbon odor
Specific Gravity	0.75
pH	Not applicable
Boiling/Cond. Point	>100°F
Solubility	Insoluble in water
Evaporation Rate (BuAc=1)	<1.00
VOC%	80
Vapor Pressure	Not applicable



DESCRIPTION

Dynatex® Red Grease is a multi-purpose lubricant that provides extra protection under extreme pressure and temperatures from 0°F to 400°F. It has excellent water resistance which makes it ideal for machinery operating in damp environments. Also, for use on bearings, automotive hinges, hitches, fifth wheels, cables, pulleys and chains.

FEATURES

- Resists washout by water, heavy loads, and pressure
- Excellent mechanical stability
- Oxidation, rust and corrosion inhibited
- Won't "pound out"
- Red color for easy identification
- Tested in accordance to 75/324/EEC Directive 6.1

TYPICAL APPLICATIONS

- Automotive hinges
- Ball and roller bearings
- Cables
- Pulleys
- Chains
- Truck fleets
- U-joints
- Fifth wheels
- Hitches
- Couplings
- Construction
- Industrial
- Agriculture
- Applications exposed to intermittent water, mud and other contamination

Packaging

Colors: Red

Size: 12 Oz Net Aerosol

STORAGE AND SHELF LIFE

Dynatex® Red Grease should ideally be stored in a cool, dry location in unopened containers at a temperature between 46°F (8°C) to 82°F (28°C) unless otherwise labeled. DO NOT store within 1 meter (4 feet) of roofline of the warehouse of storage building. Store in accordance with NFPA 30B for level 1 aerosols. *Dynatex® Red Grease* has a shelf life of 18 months from date of shipment

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 122°F (50°C). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. **DO NOT SMOKE WHILE USING THIS PRODUCT.**

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non-warranty: Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.

Dynatex® a division of **SOUDAL**

350 Ring Road
Elizabethtown, KY 42701
Email: sales@dynatex.net
Toll Free: (800) 999-2937
Ph: (270) 769-5557
Fax (270) 769-6418
Website: www.dynatex.net