

## TRUCK N' TRAILER FAST GRAB ADHESIVE PART NOS. 145765, 145764

### TYPICAL PROPERTIES

#### Uncured

|  |            |
|--|------------|
| Appearance .....                                 | Smooth     |
| Spec Gravity .....                               | 1.6        |
| Sag/Slump.....                                   | NIL        |
| Extrusion Rate .....                             | 250 g/min. |
| Tack Free Time @ 75°F (24°C)<br>And 50% RH ..... | 20min.     |

#### Cured – Physical

**7 Days @ 77°F (25°C) and 50% RH  
(1/8" thickness)**

|                                 |                |
|---------------------------------|----------------|
| Durometer Shore A Hardness..... | 48 points      |
| Tensile Strength .....          | 420 psi        |
| Elongation .....                | 480%           |
| Modulus (psi) .....             | 250 psi        |
| Solid .....                     | 98%            |
| Service Temperature .....       | -40°F to 200°F |
| Application Temperature.....    | -35°F to 140°F |



### DESCRIPTION

*Dynatex® Truck N' Trailer Fast Grab Adhesive* is a one-component, high performance adhesive/sealant formulated with USP™ Technology. It provides excellent durability, maximum adhesive strength and is VOC compliant in all 50 states. It is designed to resist all on-the- road flexing and vibration. It is fast curing and provides permanent elastic adhesion to most surfaces with quick grab and excellent durability.

### FEATURES

- VOC Compliant
- Trailer Sealant/Adhesive
- Non-Streaking or Staining
- Can be applied and tooled in most weather conditions
- Paintable\*
- No shrinking
- Flexible

\*Always test small area for compatibility before applying.

### TYPICAL APPLICATIONS

Popular applications include:

- Tractor trailers
- RV's
- Buses
- Van conversions
- Shipping containers and many other adhesive /sealant applications

### MEETS

- ASTM C920, Type S, Grade NS, Class 35, Use T, NT, M, A, G & O.
- Federal Specification TT-S-0230C, Type II, Class A

### Packaging

Colors: White, Grey  
Size: 300ml Cartridge

## STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 90°F (32°C), **Dynatex® Truck N' Trailer Fast Grab Adhesive** has a shelf life of 12 months from date of shipment.

In Countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright with the nozzle tip pointed upwards. DO NOT stack cartons on their side. **NEVER** stack cartons more than 8 high. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building.

## REMARKS

- Do not use for structural glazing.
- Not recommended for use on PE, PP or PTFE (Teflon) due to poor adhesion to these substrates
- Not recommended for applications below the water line, continuous immersion or for sealing/bonding windshields
- Poor resistance to solvents, concentrated acids and chlorinated hydrocarbons

## USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

**Non-warranty:** Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.



350 Ring Road  
Elizabethtown, KY 42701  
Email: sales@dynatex.net  
Website: www.dynatex.net

Toll Free: (800) 999-2937  
Ph: (270) 769-5557  
Fax (270) 769-6418