

Roof & Gutter Sealant Professional Grade

TECHNICAL DATA SHEET

TYPICAL PROPERTIES

Basis	Bitumen elastomer
Consistency	Stable paste
Curing system	Physical drying
Skin formation	Surface dry after 20 min.
Density	1.10 g/ml
Maximum allowed distortion	10 %
Temperature resistance**	-31°F → 176°F
Application temperature	34°F → 86°F
Shrinkage	Ca. 11%

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.

DESCRIPTION

BOSS® 241 Roof Cement is an asphalt-based one-component ready to use roof and gutter sealant formulated for use in new construction and emergency repairs for leaking roofs. It is engineered to provide exceptional sealing and bonding to dry, damp, and wet surfaces, including underwater applications. It's water-resistant properties, excellent adhesion, and UV stability make for a durable long lasting watertight repair.

BOSS® 241 Roof Cement adheres very well on bituminous substrates, and is very easy to apply, It has good adhesion to many substrates, and has high fluid resistance.

HOW TO USE

BOSS® 241 Roof Cement is supplied ready-to use. Outside use only. Clean surface, remove any soap, oil, or grease. Cut tip off cartridge just above threads. Screw on nozzle and cut to 45° angle. Insert cartridge into standard caulking gun. For smooth seal, hold at 45° angle and apply by pushing ahead of nozzle. Complete tooling within 10 minutes.

CLEAN UP

Uncured sealant can be easily removed using a solvent such as mineral spirits. For an environmental and health friendlier choice use BOSS® 893 Biggie Wipes. If the sealant is cured it must be removed mechanically by cutting and scraping.

CAUTION

Flammable liquid and vapor. May cause drowsiness or dizziness. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Wear protective gloves and eye protection / face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower. If swallowed, seek medical advice immediately and show this container or label. In case of fire: Use suitable extinguishing medium to extinguish. Dispose of contents / container in accordance with local / regional / national / international regulation. Repeated exposure may cause skin dryness or cracking.

⚠ WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

Continued...



APPLICATIONS

- Joints with movement till max. 10%
- Repair product for leaks in gutters, drainpipes and roof covers.
- Cold adhesive for all roofing types (except PDM-foil).
- Implementing emergency repairs, even in rain.

Scan the QR Code to see the full line of **BOSS® PRO** Products!



STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 90°F (32°C), **BOSS® 241** Roof Cement has a shelf life of 12 months from date of shipment. In countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright with the nozzle tip pointed upwards. **DO NOT** stack cartons on their side. **NEVER** stack cartons more than 8 high. **DO NOT** store within 1 meter (4 feet) of roofline of the warehouse or storage building.

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

TECHNICAL DATA SHEET

COLORS

- Black

PACKAGING

- 10.1 oz. Cartridge

Limited Warranty: Soudal warrants that its products will be free of defects for 3 years from the date of purchase. In the event a product does not conform to this warranty, the sole and exclusive remedy is at Soudal's option, replacement of product or refund of the purchase price. The warranty provided herein shall be void and of no effect if the product is not installed in accordance with Soudal's published instructions, listed systems, and applicable building and safety codes. This limited warranty does not cover labor, installation costs, consequential damages, or incidental damages. Under no circumstances will Soudal be liable for any amount more than the product purchase price. **THIS WARRANTY IS IN LIEU OF ALL OTHER REPRESENTATIONS AND EXPRESSED OR IMPLIED WARRANTIES** (including the implied warranties of merchantability or fitness for a particular use) **AND UNDER NO CIRCUMSTANCES SHALL SOUDAL BE LIABLE FOR A DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMITATION, AND LOSS OF REVENUE, PROFIT, OR USE.** Prior to use, the user shall determine the suitability of the product for its intended use and assumes all risks and liability for subsequent use. No person other than an officer of Soudal is authorized to bind Soudal to any other warranty for any product which this warranty is issued.



Soudal Accumetric

MADE IN POLAND

350 Ring Road
Elizabethtown, KY 42701
800-928-BOSS(2677)
270-769-3385
FAX 270-765-2412
www.bossproducts.com

BOSS is a registered trademark of Soudal