

## Door & Window Foam

### TYPICAL PROPERTIES

Density	1.56 lbs./ft <sup>3</sup>
Thermal Conductivity	0.22 - 0.26 Btu-in/hr-F-ft <sup>2</sup>
R Value	3.8 - 4.8 per inch
Tack Free (1" bead)	8 minutes (68°F & 65% RH)
Fully Cured (1" bead)	12 hours (68°F & 65% RH)
Cutable (1" bead)	1 hour (68°F & 65% RH)
Tensile Strength	15 psi
Shear Strength	7 psi
Elongation	20%
Yield / 24 Oz. Can	11 gallons freely foamed
Theoretical Yield   24 Oz. 1/4" bead	4300 ft.
Theoretical Yield   24 Oz. 1/2" bead	1030 ft.
VOC	166 g/l
Service Temperature	-40°F to 194°F
Application Temperature	40°F to 95°F

### DESCRIPTION

**BOSS® 334** Window & Door Minimal Expanding Gun Foam is a one-component, ready to use polyurethane foam, formulated to seal the gap around window and door frame and the rough opening. **BOSS® 334** expands to generate an effective seal, and when used properly is proven not to distort or bow window and door frames. **BOSS® 334** will achieve a Sound Transmission Class (STC) of 58 when applying it in accordance with ASTM C-919 "Standard Practice for use of Sealants in Acoustical Applications".

### FEATURES

- AAMA 812-04 approved
- CFC propellant free
- Excellent adhesion on most substrates (except Teflon, PE and PP)
- High thermal and acoustical insulation
- Very good filling capacities
- Excellent mounting capacities
- Excellent stability (no shrink or post expansion)
- Very precise application due to the foam gun system
- Low pressure build, reducing the chance of bowing
- VOC Compliant

### HOW TO USE

Surfaces must be clean and free of grease and dust. Spray mist into cavity prior to applying foam and in between layers to improve adhesion and speed up curing. Shake can vigorously for 30 seconds before use and regularly during use for maximum yield. Can must be held **UPSIDE DOWN** during application. Flip open cap and wear gloves provided inside cap. Unclip nozzle. Point nozzle and press trigger. Fill void 50% full to allow for expansion. For best results, use in temperatures between 41°F to 95°F.

### SPECIFICATIONS

- ASTM E-2112
- ASTM E-283
- ASTM E-331
- ASTM E-547
- ASTM C-1620
- ASTM E-84 UL 723
- AAMA 812

Continued...



### APPLICATIONS

- Installing of window and doorframes
- Filling of cavities
- Sealing of all openings in roof construction
- Creation of a soundproof screen
- Connecting of insulating materials and roof construction
- Application of a soundproofing layer on motors

Scan the QR Code to see the full line of **BOSS® PRO** Products!



# BOSS® 334 Gun Grade Foam



## CLEAN UP

Uncured sealant can be easily removed using BOSS® 335 or a solvent such as alcohol or acetone. For an environmental and health friendlier choice use BOSS® 893 Biggie Wipes. If the sealant is cured it must be removed mechanically by cutting and scraping.

## SHIPPING LIMITATIONS

Ground shipments only. Cannot ship by air. | Reactive VOC 164 g/l (16.4% wt.)

## CAUTION

**EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE.** Turn off all pilot lights, electrical igniters, burners and other sources of ignition or heat during use. Do not smoke, use matches or lighters while dispensing foam. Do not expose to direct sunlight, high heat or store in enclosed vehicle. Avoid breathing vapor/spray. Use only outdoors or in a well ventilated area with appropriate breathing apparatus. Avoid contact with skin and eyes. Wearing eyewear and gloves is recommended. Do not incinerate or puncture can. Store at temperatures below 120°F. **KEEP OUT OF REACH OF CHILDREN.** For safe handling information on this product, consult the Safety Data Sheet (SDS).

**FIRST AID:** In case of eye contact, flush immediately with water for 15 minutes and get medical help. If inhalation causes physical discomfort, move to fresh air. If discomfort persists or any breathing difficulty occurs, get medical help. If swallowed, drink large quantities of water. **DO NOT** induce vomiting. **GET PHYSICIAN ASSISTANCE IN ALL CASES.** Cured foam is not harmful to health.

**CONTAINS:** Polymethylene polyphenyl isocyanate, Dimethylether, Isobutane and Propane

## STORAGE AND SHELF LIFE

When stored upright in a dry environment at or below 70°F (21°C), **BOSS® 334** has a shelf life of 12 months from date of shipment. In countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright with the cap pointed upwards. **DO NOT** stack cartons on their side. **NEVER** stack cartons more than 8 high. **DO NOT** store within 1 meter (4 feet) of roofline of the warehouse or storage building.

## USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

## TECHNICAL DATA SHEET

### COLORS

- Tan

### PACKAGING

- 12 oz. Straw Can
- 20 oz. Genius Can
- 24 oz. Gun Grade Can



**SURFACE BURNING CHARACTERISTICS**  
Applied To Inorganic Reinforced Cement Board+  
**FLAME SPREAD: 15 / SMOKE DEVELOPED: 35**  
+ - Tested as applied in two 1 in. diameter beads, 8 in. on center, covering 11.3 percent of the exposed test sample area.



**SURFACE BURNING CHARACTERISTICS IN ACCORDANCE WITH CAN/ULC-S102**  
Applied To Inorganic Reinforced Cement Board+  
**FLAME SPREAD: 30 / SMOKE DEVELOPED: 50**  
+ - Tested as applied in two 25 mm diameter beads spaced 200 mm on center, covering 11.3 percent of the exposed test sample area.



CAULKING & SEALANTS

**Limited Warranty:** Buyer assumes all risks of use, handling and storage of product not in strict accordance with label directions. Liability for any incidental or consequential damage or loss is specifically excluded at all times. Any implied warranty of merchantability or fitness for particular use is excluded. Seller will not accept liability for more than product replacement.



**Soudal Accumetric**

MADE IN BELGIUM

350 Ring Road  
Elizabethtown, KY 42701  
800-928-BOSS(2677)  
270-769-3385  
FAX 270-765-2412  
[www.bossproducts.com](http://www.bossproducts.com)

BOSS is a registered trademark of Soudal

# Door & Window Foam

### TYPICAL PROPERTIES

Density	1.56 lbs./ft <sup>3</sup>
Thermal Conductivity	0.22 - 0.26 Btu-in/hr-F-ft <sup>2</sup>
R Value	3.8 - 4.8 per inch
Tack Free (1" bead)	8 minutes (68°F & 65% RH)
Fully Cured (1" bead)	12 hours (68°F & 65% RH)
Cutable (1" bead)	1 hour (68°F & 65% RH)
Tensile Strength	15 psi
Shear Strength	7 psi
Elongation	20%
Yield / 24 Oz. Can	4.9 gallons freely foamed
Theoretical Yield   12 Oz. 1/4" bead	1500 ft.
Theoretical Yield   12 Oz. 1/2" bead	480 ft.
VOC	235 g/l
Service Temperature	-40°F to 194°F
Application Temperature	40°F to 95°F

### DESCRIPTION

**BOSS® 334** Window & Door Minimal Expanding Straw Foam is a one-component, ready to use polyurethane foam, formulated to seal the gap around window and door frame and the rough opening. **BOSS® 334** expands to generate an effective seal, and when used properly is proven not to distort or bow window and door frames. **BOSS® 334** will achieve a Sound Transmission Class (STC) of 58 when applying it in accordance with ASTM C-919 "Standard Practice for use of Sealants in Acoustical Applications".

### FEATURES

- AAMA 812-04 approved
- CFC propellant free
- Excellent adhesion on most substrates (except Teflon, PE and PP)
- High thermal and acoustical insulation
- Very good filling capacities
- Excellent mounting capacities
- Excellent stability (no shrink or post expansion)
- Very precise application due to the foam gun system
- Low pressure build, reducing the chance of bowing
- VOC Compliant

### HOW TO USE

Surfaces must be clean and free of grease and dust. Spray mist into cavity prior to applying foam and in between layers to improve adhesion and speed up curing. Shake can vigorously for 30 seconds before use and regularly during use for maximum yield. Can must be held **UPSIDE DOWN** during application. Flip open cap and wear gloves provided inside cap. Unclip nozzle. Point nozzle and press trigger. Fill void 50% full to allow for expansion. For best results, use in temperatures between 41°F to 95°F.

### SPECIFICATIONS

- ASTM E-2112
- ASTM E-283
- ASTM E-331
- ASTM E-547
- ASTM C-1620
- ASTM E-84 UL 723
- AAMA 812

Continued...



### APPLICATIONS

- Installing of window and doorframes
- Filling of cavities
- Sealing of all openings in roof construction
- Creation of a soundproof screen
- Connecting of insulating materials and roof construction
- Application of a soundproofing layer on motors

Scan the QR Code to see the full line of **BOSS® PRO** Products!





## CLEAN UP

Uncured sealant can be easily removed using BOSS® 334 or a solvent such as alcohol or acetone. For an environmental and health friendlier choice use BOSS® 893 Biggie Wipes. If the sealant is cured it must be removed mechanically by cutting and scraping.

## SHIPPING LIMITATIONS

Ground shipments only. Cannot ship by air. | Reactive VOC 175 g/l (17.9% wt.)

## CAUTION

**EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE.** Turn off all pilot lights, electrical igniters, burners and other sources of ignition or heat during use. Do not smoke, use matches or lighters while dispensing foam. Do not expose to direct sunlight, high heat or store in enclosed vehicle. Avoid breathing vapor/spray. Use only outdoors or in a well ventilated area with appropriate breathing apparatus. Avoid contact with skin and eyes. Wearing eyewear and gloves is recommended. Do not incinerate or puncture can. Store at temperatures below 120°F. **KEEP OUT OF REACH OF CHILDREN.** For safe handling information on this product, consult the Safety Data Sheet (SDS).

**FIRST AID:** In case of eye contact, flush immediately with water for 15 minutes and get medical help. If inhalation causes physical discomfort, move to fresh air. If discomfort persists or any breathing difficulty occurs, get medical help. If swallowed, drink large quantities of water. **DO NOT** induce vomiting. **GET PHYSICIAN ASSISTANCE IN ALL CASES.** Cured foam is not harmful to health.

**CONTAINS:** Polymethylenepolyphenylisocyanate, Dimethylether, Isobutane and Propane

## STORAGE AND SHELF LIFE

When stored upright in a dry environment at or below 70°F (21°C), **BOSS® 334** has a shelf life of 12 months from date of shipment. In countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright with the cap pointed upwards. **DO NOT** stack cartons on their side. **NEVER** stack cartons more than 8 high. **DO NOT** store within 1 meter (4 feet) of roofline of the warehouse or storage building.

## USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

## TECHNICAL DATA SHEET

### COLORS

- Tan

### PACKAGING

- 12 oz. Straw Can
- 20 oz. Genius Can
- 24 oz. Gun Grade Can

 CERTIFIED UL 94 SMALL PRINT R19028 CAULKING & SEALANTS	SURFACE BURNING CHARACTERISTICS Applied To Inorganic Reinforced Cement Board+ <b>FLAME SPREAD: 15 / SMOKE DEVELOPED: 35</b> + - Tested as applied in two 1 in. diameter beads, 8 in. on center, covering 11.1 percent of the exposed test sample area.
	SURFACE BURNING CHARACTERISTICS ACCORDANCE WITH CAN/ULC-S102 Applied To Inorganic Reinforced Cement Board+ <b>FLAME SPREAD: 30 / SMOKE DEVELOPED: 50</b> + - Tested as applied in two 25 mm diameter beads spaced 200 mm on center, covering 11.1 percent of the exposed test sample area.

**Limited Warranty:** Buyer assumes all risks of use, handling and storage of product not in strict accordance with label directions. Liability for any incidental or consequential damage or loss is specifically excluded at all times. Any implied warranty of merchantability or fitness for particular use is excluded. Seller will not accept liability for more than product replacement.



**Soudal Accumetric**

MADE IN BELGIUM

350 Ring Road  
Elizabethtown, KY 42701  
800-928-BOSS(2677)  
270-769-3385  
FAX 270-765-2412  
[www.bossproducts.com](http://www.bossproducts.com)

BOSS is a registered trademark of Soudal

# Door & Window Foam

### TYPICAL PROPERTIES

Density	1.56 lbs./ft <sup>3</sup>
Thermal Conductivity	0.22 - 0.26 Btu-in/hr-F-ft <sup>2</sup>
R Value	3.8 - 4.8 per inch
Tack Free (1" bead)	8 minutes (68°F & 65% RH)
Fully Cured (1" bead)	12 hours (68°F & 65% RH)
Cutable (1" bead)	1 hour (68°F & 65% RH)
Tensile Strength	15 psi
Shear Strength	7 psi
Elongation	20%
Yield / 24 Oz. Can	6.6 gallons freely foamed
Theoretical Yield   20 Oz. 1/4" bead	2279 ft.
Theoretical Yield   20 Oz. 1/2" bead	557 ft.
VOC	175 g/l
Service Temperature	-40°F to 194°F
Application Temperature	40°F to 115°F

### DESCRIPTION

**BOSS® 334** Genius Gun® Window & Door Minimal Expanding Foam is a one-component, ready to use polyurethane foam, formulated to seal the gap around window and door frame and the rough opening. **BOSS® 334** expands to generate an effective seal, and when used properly is proven not to distort or bow window and door frames. **BOSS® 334** will achieve a Sound Transmission Class (STC) of 58 when applying it in accordance with ASTM C-919 "Standard Practice for use of Sealants in Acoustical Applications".

### FEATURES

- AAMA 812-04 approved
- CFC propellant free
- Excellent adhesion on most substrates (except Teflon, PE and PP)
- High thermal and acoustical insulation
- Very good filling capacities
- Excellent mounting capacities
- Excellent stability (no shrink or post expansion)
- Very precise application due to the foam gun system
- Low pressure build, reducing the chance of bowing
- VOC Compliant

### HOW TO USE

Surfaces must be clean and free of grease and dust. Spray mist into cavity prior to applying foam and in between layers to improve adhesion and speed up curing. Shake can vigorously for 30 seconds before use and regularly during use for maximum yield. Can must be held **UPSIDE DOWN** during application. Flip open cap and wear gloves provided inside cap. Unclip nozzle. Point nozzle and press trigger. Fill void 50% full to allow for expansion. For best results, use in temperatures between 41°F to 95°F.

### SPECIFICATIONS

- ASTM E-2112
- ASTM E-283
- ASTM E-331
- ASTM E-547
- ASTM C-1620
- ASTM E-84 UL 723
- AAMA 812

Continued...



Patent No. 10,106,309,B2

### APPLICATIONS

- Installing of window and doorframes
- Filling of cavities
- Sealing of all openings in roof construction
- Creation of a soundproof screen
- Connecting of insulating materials and roof construction
- Application of a soundproofing layer on motors

Scan the QR Code to see the full line of **BOSS® PRO** Products!





## CLEAN UP

Uncured sealant can be easily removed using BOSS® 335 or a solvent such as alcohol or acetone. For an environmental and health friendlier choice use BOSS® 893 Biggie Wipes. If the sealant is cured it must be removed mechanically by cutting and scraping.

## SHIPPING LIMITATIONS

Ground shipments only. Cannot ship by air. | Reactive VOC 175 g/l (18% wt.)

## CAUTION

**EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE.** Turn off all pilot lights, electrical igniters, burners and other sources of ignition or heat during use. Do not smoke, use matches or lighters while dispensing foam. Do not expose to direct sunlight, high heat or store in enclosed vehicle. Avoid breathing vapor/spray. Use only outdoors or in a well ventilated area with appropriate breathing apparatus. Avoid contact with skin and eyes. Wearing eyewear and gloves is recommended. Do not incinerate or puncture can. Store at temperatures below 120°F. **KEEP OUT OF REACH OF CHILDREN.** For safe handling information on this product, consult the Safety Data Sheet (SDS).

**FIRST AID:** In case of eye contact, flush immediately with water for 15 minutes and get medical help. If inhalation causes physical discomfort, move to fresh air. If discomfort persists or any breathing difficulty occurs, get medical help. If swallowed, drink large quantities of water. **DO NOT** induce vomiting. **GET PHYSICIAN ASSISTANCE IN ALL CASES.** Cured foam is not harmful to health.

**CONTAINS:** Polymethylenepolyphenylisocyanate, Dimethylether, Isobutane and Propane

## STORAGE AND SHELF LIFE

When stored upright in a dry environment at or below 70°F (21°C), **BOSS® 334** has a shelf life of 12 months from date of shipment. In countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright with the cap pointed upwards. **DO NOT** stack cartons on their side. **NEVER** stack cartons more than 8 high. **DO NOT** store within 1 meter (4 feet) of roofline of the warehouse or storage building.

## USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

## TECHNICAL DATA SHEET

### COLORS

- Tan

### PACKAGING

- 12 oz. Straw Can
- 20 oz. Genius Can
- 24 oz. Gun Grade Can



SURFACE BURNING CHARACTERISTICS  
Applied To Inorganic Reinforced Cement Board+  
**FLAME SPREAD: 15**  
**SMOKE DEVELOPED: 35**

CAULKING &  
SEALANTS

+ - Tested as applied in two 1 in. diameter beads, 8 in. on center, covering 11.1 percent of the exposed test sample area.

**Limited Warranty:** Buyer assumes all risks of use, handling and storage of product not in strict accordance with label directions. Liability for any incidental or consequential damage or loss is specifically excluded at all times. Any implied warranty of merchantability or fitness for particular use is excluded. Seller will not accept liability for more than product replacement.



**Soudal Accumetric**

MADE IN BELGIUM

350 Ring Road  
Elizabethtown, KY 42701  
800-928-BOSS(2677)  
270-769-3385  
FAX 270-765-2412  
[www.bossproducts.com](http://www.bossproducts.com)

BOSS is a registered trademark of Soudal