

Siliconized Latex Caulk

TYPICAL PROPERTIES

% Non-Volatile, by weight	82%
% Volume Shrinkage: ASTM C-733-87	29%
Weight, approximate	13.8 lb/gal (1.654 kg/L)
pH	7.0-8.7
Tack-Free Time: ASTM D-2377-84	25 minutes
Weather Resistance: ASTM C-732-82	Pass
Peel Strength: Wood	10.1 PLI
Peel Strength: Glass	9.5 PLI
Peel Strength: Aluminum	9.4 PLI
Service Temperature	0°F to 80°F
Tested To Application Temperature	40°F to 110°F

DESCRIPTION

BOSS® 360 Siliconized Latex Caulk is a mildew resistant, paintable, air seal and weatherization sealant formulated to provide long lasting, flexible, weatherproof seals between most common building materials including wood, masonry, concrete, brick, drywall, metal and glass. Its smooth, creamy consistency makes **BOSS® 360** easy to tool, and cures to a tough flexible seal. **BOSS® 360** can be used for both interior and exterior applications.

FEATURES

- Easy to tool
- Sealing around window and door frames
- Sealing around baseboards
- Sealing around trim
- Sealing corner Joints
- Sealing where siding meets trim
- Interior & exterior applications

HOW TO USE

BOSS® 360 Siliconized Latex Caulk should only be used where slight joint movement is anticipated. In joints exceeding 1-1/2" in depth use a foam joint filler.

Tooling is recommended and, if possible, should be completed in one continuous stroke.

Tool joints within 10 minutes of application. If masking tape has been used to obtain a cleaner joint, it should be removed before the tack-free skin forms.

CAUTION: Do not apply when building material or air temperature is below 40°F. **BOSS® 360** Siliconized Latex Caulk is not recommended for continuous water immersion or vehicular or foot traffic.

SPECIFICATIONS

- ASTM Specification C-834 grade NF

PAINTABILITY

A minimum of 2 hours dry time is required before painting with latex or oil base paint. Allow extra dry time during periods of high humidity and/or cool temperatures



APPLICATIONS

- Door & Window Frames
- Baseboards
- Trims
- Corner Joints
- Siding/Trim Abutments
- Wood
- Masonry
- Concrete
- Brick
- Drywall
- Metal
- Glass

Scan the QR Code to see the full line of **BOSS® PRO** Products!



Continued...

CLEAN UP

Uncured sealant can be easily removed using a solvent such as alcohol or acetone. For an environmental and health friendlier choice use BOSS® 893 Biggie Wipes. If the sealant is cured it must be removed mechanically by cutting and scraping.

SHIPPING LIMITATIONS

None | Nonreactive VOC 10 g/l (<1.5% wt)

CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 90°F (32°C), **BOSS® 360** Siliconized Latex Caulk has a shelf life of 12 months from date of shipment. In countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright with the nozzle tip pointed upwards. DO NOT stack cartons on their side. **NEVER** stack cartons more than 8 high. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building. **KEEP FROM FREEZING.**

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

TECHNICAL DATA SHEET

COLORS

- White

PACKAGING

- 9.5 oz. Cartridge
- 4.5 Gallon Pail
- 48 Gallon Drum

Limited Warranty: Buyer assumes all risks of use, handling and storage of product not in strict accordance with label directions. Liability for any incidental or consequential damage or loss is specifically excluded at all times. Any implied warranty of merchantability or fitness for particular use is excluded. Seller will not accept liability for more than product replacement.



Soudal Accumetric

MADE IN U.S.A.

350 Ring Road
Elizabethtown, KY 42701
800-928-BOSS(2677)
270-769-3385
FAX 270-765-2412
www.bossproducts.com

BOSS is a registered trademark of Soudal