

100% Acrylic Caulk

TYPICAL PROPERTIES

% Non-Volatile, by weight	77%
Weight, approximate	13 lb./gal. 1.558 kg/L
pH	8.0
Tack-Free Time	<25 minutes
Peel Strength - Wood	17.0 pounds-force
Peel Strength - Glass	28.0 pounds-force
Peel Strength - Aluminum	28.0 pounds-force
Low Temperature Flexibility	PASS
VOC	28 g/l
Service Temperature	-20°F to 185°F
Application Temperature	40°F to 110°F

DESCRIPTION

BOSS® 362 100% Acrylic Tub 'N' Tile Caulk was developed for use around showers, baths, tubs, tiles, backsplashes and sinks. Due to its excellent adhesion and flexibility it can be used on baseboards, door frames, windows, crown molding and any joint or gap where a weathertight mildew-resistant seal is needed.

HOW TO USE

BOSS® 362 100% Acrylic Tub 'N' Tile Caulk should only be used where moderate joint movement is anticipated. In joints exceeding 1-1/2" in depth use a foam joint filler.

Tooling is recommended and, if possible, should be completed in one continuous stroke.

Tool joints within five minutes of application. If masking tape has been used to obtain a cleaner joint it should be removed before the tack-free skin forms.

CAUTION: Do not apply when building material or air temperature is below 40°F. **BOSS® 362** 100% Acrylic Tub 'N' Caulk is not recommended for continuous water immersion or vehicular or foot traffic.

PAINTABILITY

A minimum of 2 hours dry time is required before painting with latex or oil base paint. Allow extra dry time during periods of high humidity and/or cool temperatures.

CLEAN UP

Uncured sealant can be easily removed using warm water or BOSS® Biggie Wipes. If the sealant is cured it must be removed mechanically by cutting and scraping.

SHIPPING LIMITATIONS

None | Nonreactive VOC 28 g/l (<1.5% wt.)

CAUTION

DIRECT CONTACT OF UNCURED SEAL-ANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).


Continued...



APPLICATIONS

- Sealing around sinks
- Sealing around backsplashes
- Sealing around showers, baths and tubs
- Sealing corner joints, baseboards and trim
- Sealing around tiles
- Sealing anywhere a weathertight seal is desired
- MANY MORE...

Scan the QR Code to see the full line of **BOSS® PRO** Products!



STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 90°F (32°C), **BOSS® 362** 100% Acrylic Tub 'N' Tile Caulk has a shelf life of 12 months from date of shipment. In countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright with the nozzle tip pointed upwards. **DO NOT** stack cartons on their side. **NEVER** stack cartons more than 8 high. **DO NOT** store within 1 meter (4 feet) of roofline of the warehouse or storage building.

KEEP FROM FREEZING.

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

TECHNICAL DATA SHEET

COLORS

- Clear

PACKAGING

- 5.5 oz. Tubes

Limited Warranty: Buyer assumes all risks of use, handling and storage of product not in strict accordance with label directions. Liability for any incidental or consequential damage or loss is specifically excluded at all times. Any implied warranty of merchantability or fitness for particular use is excluded. Seller will not accept liability for more than product replacement.



Soudal Accumetric

MADE IN U.S.A.

350 Ring Road
Elizabethtown, KY 42701
800-928-BOSS(2677)
270-769-3385
FAX 270-765-2412
www.bossproducts.com

BOSS is a registered trademark of Soudal