

COPPER ANTI-SEIZE SPRAY PART NO. 167359

TYPICAL & CHEMICAL PROPERTIES

Appearance/ 20°C	Liquid
Color	Copper
Odor	Characteristic
Boiling point/ range	-42°C - 95°C
Lower explosive limit (Vol %)	1.100%
Upper explosive limit (Vol %)	9.500%
Flash point	-20°C
Auto-ignition temperature	365°C
Kinematic viscosity, 40°C	270 mm ² /S
Solubility in water	Not soluble
Vapor pressure, 20°C	853,000 Pa
Relative density, 20°C	0.7400 kg/l
Dynamic viscosity, 20°C	200 mPa.s
Evaporation rate (n-BuAc = 1)	7.000
Volatile organic component (VOC)	75.09%
Volatile organic component (VOC)	475.239 g/l



DESCRIPTION

Dynatex® Copper Anti-Seize Spray is a high temperature Anti-Seize lubricant. Which consists of copper particles in bentonite grease. It is designed to control pitting, rusting, thread distortion and seizure due to corrosion and chemical attack.

FEATURES

- High heat protection up to 2000°F
- Lowers friction and reduces torque
- Compatible with all metals
- Prevents seizure and speeds assembly
- Protects against rust and corrosion

TYPICAL APPLICATIONS

Dynatex® Copper Anti-Seize Spray is used in applications subject to high friction:

- Pipe fittings
- Bolts
- Spark plug threads
- Exhaust assemblies
- Threaded connections
- Gaskets
- Wheel nuts and more....

DIRECTIONS

Surfaces to be treated should be clean and dry. SHAKE WELL BEFORE USE. Hold can upright 6-12 inches from surface and apply a continuous coating over the mating surfaces.

Packaging

Colors: Copper

Size: 10.67 Oz Net

STORAGE AND SHELF LIFE

Dynatex® Copper Anti-Seize Spray should ideally be stored in a cool, dry location in unopened containers at a temperature between 46°F (8°C) to 82°F (28°C) unless otherwise labeled. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building. **Dynatex® Copper Anti-Seize Spray** has a shelf life of 18 months from date of shipment

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 122°F (50°C). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. **DO NOT SMOKE WHILE USING THIS PRODUCT.**

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non-warranty: Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.



350 Ring Road
Elizabethtown, KY 42701
Email: sales@dynatex.net

Toll Free: (800) 999-2937
Ph: (270) 769-5557
Fax (270) 769-6418
Website: www.dynatex.net