



SODAL



TECHNICAL DATA SHEET

COPPER HI-TACK GASKET SPRAY PART NO. 173320

PHYSICAL PROPERTIES

Appearance.....	Liquid
Color	Copper
Odor	Solvent
Boiling point/ Boiling range (Acetone)	56°C
Flash point (Acetone)	-17°C
Exposure limit ranges (Propane) ...	2.1% - 9.5%
Vapor pressure (Propane)	ca. 95 x 10 ⁴
Density	0.86
Auto ignition temperature (Acetone)	465°C
Decomposition temperature	<20°C
Kinematic viscosity.....	<20
VOC Content	730 g/L (85%)

DESCRIPTION

Dynatex® Copper Hi-Tack Gasket Spray dries quickly to a highly tacky elastomeric film. This product was specifically designed to hold the heaviest gaskets in place during assembly. It is oxygen sensor safe, highly resistant to automotive fuels and oils and it remains tacky indefinitely. Product can be applied in advance for convenience in assembly.

FEATURES

- Dries fast to a highly tacky, elastomeric film
- Oxygen sensor safe
- Highly resistant to automotive fuels and oils
- Remains tacky indefinitely – can be applied in advance for convenience in assembly
- Temperature range -65°F to 450°F

TYPICAL APPLICATIONS

Bond and seal any type of cut gasket including:

- Rubber
- Felt
- Cork
- Paper
- Metal

DIRECTIONS FOR USE:

1. Shake well with repeated agitation.
2. Holding can 6 to 10 inches from the surface to be coated, with can in upright position, press the nozzle and spray the product uniformly. Apply a thin even coat to both flange surfaces, both sides of gasket material and attaching bolt threads.
3. Allow sprayed material to sit for a few minutes before assembly. Gaskets may

FOR CLEANUP

1. Turn can upside-down and spray to clear nozzle.
2. Clean hands with **Dynatex® Abrasive Wipes**, P/N 143559.

PACKAGING

Color: Copper

Packaging: 9 Oz Net Aerosol

STORAGE AND SHELF LIFE

Dynatex® Copper Hi-Tack Gasket Spray should ideally be stored in a cool, dry location in unopened containers at a temperature between 46°F (8°C) to 82°F (28°C) unless otherwise labeled. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building. Store in accordance with NFPA 30B for level 3 aerosol. **Dynatex® Copper Hi-Tack Gasket Spray** has a shelf life of 12 months from date of shipment

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 122°F (50°C). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non-warranty: Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.



350 Ring Road
Elizabethtown, KY 42701
Email: sales@dynatex.net

Toll Free: (800) 999-2937
Ph: (270) 769-5557
Fax (270) 769-6418

Website: www.dynatex.net