

# T-REX GRAB SUBFLOOR

Revision: 05/3/24

Page 1 of 2

**Technical Data:**

Basis	Synthetic rubber
Consistency	Paste
Curing system	Physical drying and crystallisation
Curing speed *	Hand tight in 20 min.
Temperature resistance**	-4°F → 140°F
Open time (*)	Ca. 15 min.
Curing time	Full cure up to 7 days
Application temperature	41°F → 86°F Product Description

\* The values indicated may vary depending on environmental conditions such as temperature, humidity, nature of the supports. \*\*Information is for fully cured product.

**Product Description:**

T-Rex Grab Subfloor Adhesive is a solvent-based high performance adhesive designed with strong initial tack and excellent adhesive strength making it the ideal product for subfloor installations. The resulting permanent bond remains flexible to prevent squeaky floors and reducing nailing. T-Rex Subfloor Adhesive can be used for bonding most construction materials (porous and non-porous) for both interior and exterior applications.

**Properties:**

- Universal use
- Suitable for bonding on uneven surfaces.
- Makes the use of screws and nails redundant.
- Water resistant
- Suitable for bonding polystyrene

**Applications:**

- All bonding in assembly techniques.
- Bonding in the renovation industry.
- Bonding in construction industry.
- Bonding of cable trays and panels.

**Packaging:**

10.1 fl oz Cartridge

**Shelf life:**

12 months in unopened packaging in a cool and dry storage place at temperatures between 41°F and 77°F.

**Substrates:**

*Nature:* clean, free of dust and grease.

*Surface preparation:* No pretreatment required. T-Rex Grab Subfloor has excellent adhesion on most substrates. *There is no adhesion on PE, PP, PTFE (Teflon®) and bituminous substrates. We recommend a preliminary adhesion test on any substrate.*

**Application method:**

Surfaces must be clean, dry, structurally sound, and free from dust and grease. Application is best performed at 41°F to 86°F. Cut nipple off cartridge and attach nozzle. Cut nozzle to desired bead size (1/4" to 3/8") and place into a caulking gun. Apply a bead in a zig zag pattern on all joists/studs. Place subfloor sheeting within 15 minutes of application. Press firmly on the sheeting to ensure full contact with the adhesive. Use mechanical fasteners to screw down the subfloor panel as recommended by the American Plywood Association. This product has not been designed for continuous immersion.

*Clean Up:* Wet adhesive can be cleaned with acetone, mineral spirits or SWIPEX. Dry adhesive should be removed mechanically.

*Repair:* With the same material.

**Specifications:**

AFG-01, ASTM C557, ASTM D3498

Remark: This information and all further technical advice are based on SOUDAL present knowledge and experience. However, SOUDAL assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, SOUDAL disclaims all WARRANTIES EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. SOUDAL SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. SOUDAL reserves the right to make any changes according to technological progress or further developments.

---

## T-REX GRAB SUBFLOOR

---

Revision: 05/3/24

Page 2 of 2

### Health- and Safety Recommendations:

Take the usual labour hygiene into account. Consult label and material safety data sheet for more information.

### Limited Warranty:

Soudal warrants product to be of good quality and will replace or, at our election, refund the purchase price of any products proved to be defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, Soudal makes no warranty or guarantee, expressed or implied, including warranties of fitness for a particular purpose or merchantability, respecting its products, and Soudal shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith.

Remark: This information and all further technical advice are based on Soudal present knowledge and experience. However, Soudal assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, Soudal disclaims all warranties express or implied, including the implied warranties of fitness for a particular purpose or merchantability. Soudal shall not be responsible for consequential, indirect or incidental damages (including loss of profits) of any kind. Soudal reserves the right to make any changes according to technological progress or further developments.

Distributed by: Soudal Accumatic • Elizabethtown, KY 42701 • [www.soudalusa.com](http://www.soudalusa.com) • [info@soudalusa.com](mailto:info@soudalusa.com) • 877-873-8739