

T-REX GRAB SUPER GRAB

Revision: 05/3/24

Page 1 of 2

Technical Data:

Base	Acrylic
Consistency	Smooth Homogenous Paste
Color	White
Curing System	Physical Drying
Density	Ca. 1.30 g/ml
Open time*	15 min.
Drying time*	24 h → 48 hV
Initial adhesion	Minimum 140kg/m ²
Temperature resistance**	-4°F → 158°F
Application temperature	41°F → 86°F

* Testing completed at 73°F and 55% RH. The values indicated may vary depending on environmental conditions such as temperature, humidity, and nature of the supports.

Product Description:

T-Rex Grab Drywall Adhesive is a powerful, ready-to-use, water-based universal fixing adhesive that is characterised by an extremely high initial adhesion (more than 140 kg/m²) and a high final strength.

Characteristics:

- Solvent-free
- Initial adhesion: 140 kg/m² (full surface bonding)
- Bonding on irregular substrates
- Apply unilaterally
- Moisture resistant
- Can be coated with water-based paints

Applications:

- Especially suitable for porous substrates.
- Very good adhesion to all common porous building substrates.
- Suitable for the solid fixing of materials such as wood, plastics, stone, wall tiles or metal, on substrates made of concrete, stone, plaster, wood, chipboard, etc.
- Suitable for bonding, among other things, panelling, wooden or PVC skirting boards, cable ducts as well as the most common decorative materials.

Packaging:

10.1 fl oz.

Shelf life:

At least 12 months in its original packaging closed, in a dry place, at a temperature between 41 and 77°F.

Surfaces:

Types: All common building supports

Condition: Clean, Dusted and Degreased. At least one of the materials to be bonded must be porous.

Pre-treatment: No pre-treatment required.

There is no adhesion on PE, PP, PTFE (Teflon®) and bituminous surfaces. It is advisable to do a preliminary adhesion test on any substrate.

How to use:

Method of application: All surfaces must be clean, dry, structurally sound, and free from dust and grease.

Application is best performed at 41°F and 86°F. Cut nipple off cartridge and attach nozzle. Cut nozzle to desired bead size (1/4" to 3/8") and place into caulking gun. Apply bead in a zigzag pattern on all studs. Place drywall sheeting within 15 minutes of application. Press firmly on the drywall to ensure full contact with the adhesive. Use mechanical fasteners to screw down the drywall. This product is not recommended for continuous immersion.

Cleaning: T-Rex Grab Drywall Adhesive can be removed from tiles and tools with water as long as the product has not hardened. T-Rex Grab Drywall Adhesive rugged can only be removed mechanically.

Repair: With the same product.

Safety Recommendations:

Observe the usual occupational hygiene. Wash hands after use. For additional information, see SDS.

Remark: This information and all further technical advice are based on SOUDAL present knowledge and experience. However, SOUDAL assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, SOUDAL disclaims all WARRANTIES EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. SOUDAL SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. SOUDAL reserves the right to make any changes according to technological progress or further developments.

T-REX GRAB SUPER GRAB

Revision: 05/3/24

Page 2 of 2

Specifications:

ASTM C557

Remarks:

- When bonding, it is the power and not the duration of compression that determines the final force.
- Do not use in prolonged contact with water.

Limited Warranty:

Soudal warrants product to be of good quality and will replace or, at our election, refund the purchase price of any products proved to be defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, Soudal makes no warranty or guarantee, expressed or implied, including warranties of fitness for a particular purpose or merchantability, respecting its products, and Soudal shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith.

Remark: This information and all further technical advice are based on Soudal present knowledge and experience. However, Soudal assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, Soudal disclaims all warranties express or implied, including the implied warranties of fitness for a particular purpose or merchantability. Soudal shall not be responsible for consequential, indirect or incidental damages (including loss of profits) of any kind. Soudal reserves the right to make any changes according to technological progress or further developments.