ACCESSORIES

SOUDAL SWIPEX
SUPER CLEANING WIPES



Swipex are solvent based cleaning wipes for uncured sealants & adhesives.

- Non woven wipes impregnated with a mixture of solvents, biodegradable non-ionic surfactants and skin emollients
- Suitable for all non-porous surfaces
- For hands and tools
- Cleans uncured sealant
- Removes oil, adhesive, etc.

AVAILABLE IN:
TUB 100 COUNT 113551

SOUDAL GUN & FOAM CLEANER
SPRAY




Soudal Gun & Foam Cleaner is a solvent cleaner specifically designed for cleaning of uncured PU foam.

- For hands and tools
- Cleans uncured PU foam

AVAILABLE IN:
AEROSOL CAN 12 OZ. 120319

GUNS



Soudal Skeleton Gun
10 oz Cartridge
106966



Soudal Heavy Duty Skeleton Gun
10 oz Cartridge
106617



Soudal Compact Gun
is a **plastic** gun foam applicator
109953



Soudal Designer Gun
is a top of the line **metal** gun foam applicator
154478



Soudal Designer Gun 22"
is a **22"** long top of the line **metal** gun foam applicator
122129

20-Year SOUDAL Limited Warranty for Window & Door Installation Systems

WHAT DOES THIS 20-YEAR SOUDAL LIMITED WARRANTY COVER?

The 20-Year Soudal Limited Warranty covers the performance of the complete Soudal Window & Door Installation System, including sealants, foams, flashing, and related components, when installed in accordance with Soudal published installation guidelines, applicable building codes, and industry standards (including ASTM and AAMA). The system must be used in new or replacement residential or light commercial construction.

The warranty guarantees that the system will prevent water and moisture intrusion between the exterior surface of the window or door frame and the interior surface of the rough opening. Manufacturer retains discretion to investigate any and all claims of performance failure. If the system fails to perform as specified, validated by inspection at the sole discretion of the manufacturer, the manufacturer may, at its sole discretion, reimburse the original purchaser for the reasonable cost of labor and materials to repair or replace the affected area, up to a maximum of $10,000 per dwelling unit.

HOW LONG DOES COVERAGE LAST?

Coverage begins on the date of original installation and continues for a period of twenty (20) years. This warranty is non-transferable and applies only to the original purchaser.

WHAT IS NOT COVERED?

This warranty does not apply to damage or failure resulting from:

- Improper installation, storage, handling, or use of the system or its components
- Use of non-approved or incompatible materials
- Structural movement, settlement, or design flaws
- Acts of God (e.g., hurricanes, floods, earthquakes, tornadoes, lightning)
- Mold, mildew, fungi, bacteria, or other biological growth
- Normal weathering, fading, chalking, or cosmetic changes
- Unauthorized modifications or repairs
- Use in wall systems that do not allow for proper moisture management (e.g., EIFS without drainage)
- Failure to maintain the installation in accordance with industry standards

DISCLAIMER OF WARRANTIES

EXCEPT AS EXPRESSLY PROVIDED HEREIN, THE MANUFACTURER DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AND REMEDIES.

THIS WARRANTY IS VOID WHERE PROHIBITED BY FEDERAL, STATE OR LOCAL LAW AND GOVERNED BY KENTUCKY LAW.

LIMITATION OF LIABILITY

IN NO EVENT SHALL THE MANUFACTURER BE LIABLE FOR INCIDENTAL, SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES, INCLUDING BUT NOT LIMITED TO LOSS OF USE, PROFITS, OR PROPERTY DAMAGE. LIABILITY IS LIMITED TO THE REMEDIES EXPRESSLY SET FORTH IN THIS WARRANTY.

HOW TO MAKE A CLAIM

All warranty claims must be submitted in writing within 30 days of discovery of the issue. Claims must include:

- Proof of purchase and installation date
- Description of the issue and affected area
- Photographic documentation
- Access for inspection and/or testing if requested

Submit claims to:
Warranty Claims Department
[Manufacturer Name]
[Address]
[Email Address]
[Phone Number]



SOUDAL
Soudal Accumetric
350 Ring Road • Elizabethtown - KY 42701 • USA
Tel.: +1-877-873-8739 • info@soudalusa.com • www.soudalusa.com



SOUDAL

SOUDAL WINDOW SYSTEM PRODUCT LINE - INSTALLATION

With heating and cooling costs skyrocketing, leaky buildings can be a big drain on a homeowner's budget. Air leakages (in- and exfiltration) are a big waste of energy and money, as are uninsulated or under insulated windows. Installing energy-efficient windows and doors can greatly reduce this energy loss, but the area around the window and door frames is often overlooked, still resulting in air leakages and thermal bridges. Your new windows will never perform well without proper installation!

The low expansion foam formulations of Soudal's foams differentiates it from other polyurethane foams. Closing the gap with the Soudal Window System not only helps to reduce energy costs, it also helps with the thermal and acoustic insulation, vapor diffusion and the watertightness of the window. It also enhances comfort and helps with the esthetic beauty of the window frame. SWS is active on three levels. When installed properly, SWS offers include: seal and vapor isolation on the inside, optimal thermal and acoustic insulation in the middle of the wall and, wind and weather protection on the outside of the wall.



***Soudafoam Gun Applied Versions of Door & Window, All Season and Flex all meet:** ASTM C1620: Standard Specification for Aerosol Polyurethane and Aerosol Latex Foam Sealants • ASTM E84: Standard Test Method for Surface Burning Characteristics of Building Materials • AAMA 812-16: Standard Practice for Assessment of Single Component Aerosol Expanding Foams for Sealing Rough Openings of Fenestration Installations • UL 723: Surface Burning Characteristics of Building Materials • UL 1715: Fire Test of Interior Finish Material

SOUDACRYL LTX1
SILICONIZED LATEX ACRYLIC



Ideal for interior sealing of windows & doors

- High Quality Siliconized Acrylic Sealant
- Plasto-Elastic
- Paintable
- Colors: White, Almond, Bronze, Brown, Grey, Cedar & Clear
- Odorless
- UV and Weather Resistant
- Used for Sealing of Low Stressed Joints and Cracks
- Meets or Exceeds ASTM C-834

AVAILABLE IN: 10.1 FL. OZ. CARTRIDGE

SOUDATIGHT HYBRID
HYBRID POLYMER PASTE



Ideal for sealing gaps in walls, roofs, anf floors to prevent air leakage and improve insulation

- Sprayable, Paintable, Trowelable
- Driving Rain Tight, Airtight
- Vaper Permeable
- Forms a Seamless Membrane

AVAILABLE IN:
6KG PAIL & 20 FL. OZ. SAUSAGE 000000

SOUDASTRETCH
100% FLEXIBLE ELASTOMERIC SEALANT



Ideal for both interior and exterior use

- Paintable
- Very smooth formula
- Handles up to 5 freeze-thaw cycles
- Easy clean-up with water
- Low odor
- VOC compliant
- Mildew resistant
- Excellent adhesion to wood, masonry, brick, concrete, drywall, metal, glass & many more
- Meets ASTM C-920

AVAILABLE IN:
10.1 FL. OZ. CARTRIDGE

SOUDAFOAM DOOR & WINDOW*
POLYURETHANE FOAM INSULATION



Ideal for eliminating thermal bridges between window frame and construction

- Minimal Expansion Foam
- Professional Gun Grade
- Excellent Thermal and Acoustic Insulation Properties
- Closed Cell Foam: Airtight and Weather-tight Seal
- Installs 5x Faster Than Fiberglass
- Has an R-value per inch of R-6.5 Compared to R-3.14 For Traditional Fiberglass
- AAMA certified

AVAILABLE IN:
AEROSOL CAN 24 OZ. 116889
GENIUS GUN 20 OZ. 128990
STRAW 12 OZ. 128665

SOUDAFOAM FLEX*
POLYURETHANE EXTREME FLEXIBLE FOAM INSULATION



Ideal where a foam with extreme elasticity is needed

- Minimal Expansion Foam
- Very High Elastic Recovery
- Extreme Weather Formulation
- Gunable in All Seasons (-13˚F to 120˚F With a Can Temperature of 40˚F to 95˚F)
- 2 Year Shelf Life
- Storage in All Positions
- Excellent Thermal and Acoustical Insulation
- Closed Cell Foam: Airtight and Weather-tight Seal
- Installs 5x Faster Than Fiberglass
- Has an R-value per inch of R-6.5 Compared to R-3.14 For Traditional Fiberglass
- No shrinkage
- AAMA certified

AVAILABLE IN:
AEROSOL CAN 24 OZ. 128487

SOUDAFOAM ALL SEASON*
POLYURETHANE EXTREME WEATHER FOAM



Top of the line, minimal expansion foam for use in extreme climates

- Minimal Expansion Foam
- Extreme Weather Formulation
- Extra High Yield
- Gunable in All Seasons (-13˚F to 120˚F With a Can Temperature of 40˚F to 95˚F)
- Excellent Thermal and Acoustical Insulation
- Closed Cell Foam: Airtight and Weather-tight Seal
- Installs 5x Faster Than Fiberglass
- Has an R-value per inch of R-6.5 Compared to R-3.14 For Traditional Fiberglass
- No shrinkage
- AAMA certified

AVAILABLE IN:
AEROSOL CAN 24 OZ. 128390

SOUDASEAL 230HM*
ALL PURPOSE SMX®-POLYMER HYBRID SEALANT & ADHESIVE



Ideal for sealing of windows & doors, both interior and exterior

- Next Generation Sealant: Features Superior Performance Characteristics
- Both Interior and Exterior
- Superior Weather Resistance: Waterproof, Can be Applied to Damp Surfaces
- Paintable (Water Base Paint). Prior Testing Required
- Permanent Flexibility and Elasticity: +/-50% Movement
- Excellent Adherence to Porous and Non Porous Substrates: PVC-Vinyl, Wood, Glass, Metal, Concrete, Stone and Flashing Tape. No Need for Primers
- No Shrink, No Smell, No Bubbling, Easy to Tool and Finish
- Environmentally Friendly: No Isocyanates/No Solvents
- Low Temperature Workability. Will Not Freeze and Easy to Extrude
- VOC Compliant: Low VOC Level: <3% VOC
- Plastic Cartridge
- AAMA certified

AVAILABLE IN: 10.1 FL. OZ. CARTRIDGE

SOUDASIL 400N1
ONE PART, NEUTRAL CURE SILICONE SEALANT



Ideal for window glazing as well as window and door installations

- Excellent Adherence to PVC-Vinyl, Glass, Metals and Wood
- Permanent Flexibility and Excellent Recovery: +/- 50% movement
- Excellent UV Resistance, Color Stability and Weatherability
- Low Odor / VOC Compliant: Low VOC <3%
- AAMA certified

AVAILABLE IN:
10.1 FL. OZ. CARTRIDGE

***Soudaseal 230HM meets:** ASTM C920, Class 35: Standard Specification for Elastomeric Joint Sealants • AAMA 803.3-10 Type I, Validated AAMA Component as Narrow Joint Seam Sealer per Specification • AAMA 808.3-10 EXTERIOR PERIMETER SEALING COMPOUND

SOUDAL

COLOR SERVICE PROGRAM

GET THE COLOR YOU NEED

We Offer a Variety of INTERIOR & EXTERIOR Color Choices

Scan below for a full list of color matches

color match

400N1	230HM	Color
142502	173277	RAL9016
142739	174614	SCP9906
142791	173559	RAL9017
142506	173588	SCP1901
142510	173562	RAL1013
142731	173690	SCP8904
142530	174539	SCP1933
161896	173817	RAL8017
142547	173560	RAL8022
142507	174357	SCP1931

